



EXECUTIVE OFFICE: NEWARK, NJ 07105
 PHONE: 973-589-9150 FAX: 973-589-4432
MIDWEST OFFICE: TOLEDO, OH 43605
 PHONE: 419-691-2491 FAX: 419-693-3806
TECHNICAL SERVICE PHONE NO. 800-347-5343

LUBRIPLATE AERO

LUBRIPLATE Aero is a neutral lithium base lubricant, manufactured with a light viscosity mineral oil that remains plastic down to -70°F, has an ASTM Dropping Point of over 350°F and is an NLGI No. 1 consistency.

LUBRIPLATE Aero is recommended for a large variety of applications:

- Trailer landing gear cases.
- Speedometers, odometers and tachometers.
- Parking meters -- Change boxes.
- Instruments -- Gaming machines.
- Garage and door opening mechanisms.
- Cables of various types.
- Steering columns and gear cases.
- TV antenna gear boxes.
- O-Ring and seal lubrication.
- Railway switch and signal equipment.

Advantages

- Low Torque start-up capability.
- Corrosion and oxidation resistant.
- Long lasting film strength over a wide temperature range.
- Outstanding aniline point of base oil offers excellent compatibility with exotic metals, plastics and rubber materials.

Typical Tests

Type of Base	Lithium
Worked Penetration @ 77°F	310 to 340
NLGI No.	1
Mineral Oil Viscosity	
SUS @ 100°F	100
cSt @ 40°C	19
Aniline Point	205+
ASTM Dropping Point	350°F/177°C
Norma Hoffman Oxidation Bomb	Less than 5 psi/1000 Hours
Color	Off-White

(over)

Packaging Available

Part No.

Carton 24/14 oz. Cans	L0113-001
Carton 6/6 lb. Cans	L0113-006
35 lb. Pail	L0113-035
115 lb., Quarter Size, Drum	L0113-039
400 lb., Full Size, Drum	L0113-040
Carton 288 - 3/8 oz. Tubes	L0113-076
Carton 36 - 1 ³ / ₄ oz. Tubes (1x6)	L0113-086