

## Communication and Control Cable

### Description:

- Multiple conductor unshielded
- ASTM bare copper
- PVC insulation
- Twisted pair
- Overall 75° PVC jacket

### Rating as per NEC:

- UL or C(UL)<sup>+</sup> listed NEC Type CMR
- Constructed in accordance with UL Standard 444
- Complies with UL 1666 Vertical Shaft (riser) Flame Test
- Temperature range: -20° C to 75° C dry locations
- Meets 300 volt requirements as specified in section 800-51 of the NEC

### Applications:

Indoor (non-conduit per NEC) for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-Limited Control Circuits

### Color Code:

Conductors: 1. Black, 2. Red

Jacket: Gray, White, Brown

### Special Notes:

<sup>+</sup>C(UL) CMR Canadian UL accepted mark  
replaces PCC-FT4



Construction	
Number of Pairs	1
AWG Size	22
Stranding	7 x 30
Nom. Insulation Thickness	.010 inch (.25 mm)
Nom. Jacket Thickness	.015 PVC (.38 mm)
Nominal O.D.	.127 (3.23 mm)
Nom. D.C. R. Resistance @ 20°	17 Ω per 1000 Feet

**CAUTION:** Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.

**WEST PENN WIRE/CDT**  
CABLE DESIGN TECHNOLOGIES

724-222-7060  
FAX: 724-222-6420

P. O. Box 762, 2833 West Chestnut St.  
Washington, PA 15301

TOLL FREE: 800-245-4964  
PA CALL: 800-222-8883