



Communication and Control Cable

Description:

- ASTM Bare Copper
- PVC Insulation
- Short overall twist lengths
- Unshielded construction
- Overall 75° C PVC jacket

Rating:

- UL or C(UL) listed NEC Type CMR
- Constructed in accordance with UL Standard 444
- Complies with UL 1666 Vertical Shaft (riser) Flame Test
- Temperature range -20° C to 75° C dry locations
- Meets 300 volt requirements as specified in 800 of the NEC

Applications:

Indoor (non-conduit per NEC) for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-Limited Control Circuits

Overall Jacket Color: Gray

Color Code:

Conductors: 1. Black, 2. Red



| Construction | |
|-------------------------------|-------------------------|
| Number of Conductors | 2 |
| AWG Size | 20 |
| Stranding | 20 (7x28) |
| Nom. Insulation Thickness | .010 inch (.25 mm) |
| Nom. Jacket Thickness | .015 PVC (.38 mm) |
| Nominal O.D. | .141 (3.58 mm) |
| Nom. D.C. R. Resistance @ 20° | 10.5 Ω per 1000 Feet |

CAUTION: Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.