

Communication and Control Cable

Description:

- Multiple conductor unshielded
- ASTM bare copper
- PVC insulation
- Cabled Construction
- Overall 75° PVC jacket



Rating as per NEC:

- UL or C(UL)⁺ listed NEC Type CMR
- Constructed in accordance with UL Standard 444
- Complies with UL 1666 Vertical Shaft (riser) Flame Test
- Temperature range: -20° C to 75° C dry locations
- Meets 300 volt requirements as specified in section 800-51 of the NEC

Applications:

Indoor (non-conduit per NEC) for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Power-Limited Control Circuits

Color Code:

Conductors: 1. Black, 2. Red, 3. White, 4. Green

Jacket: Gray

Special Notes:

⁺C(UL) CMR Canadian UL accepted mark replaces PCC-FT4

Construction	
Number of Conductors	4
AWG Size	20
Stranding	7 x 28
Nom. Insulation Thickness	.010 inch (.25 mm)
Nom. Jacket Thickness	.015 PVC (.38 mm)
Nominal O.D.	.173 (4.39 mm)
Nom. D.C. R. Resistance @ 20°	10.5 Ω per 1000 Feet

CAUTION: Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.