

Plenecon II Extra Flexible Plenum Cable Multiple Pair Cables Unshielded

Description:

- ASTM bare copper
- Polymer alloy insulation
- Two conductors twisted to form a pair
- Overall shield coverage 100% Aluminum Polyester Foil
- Flexible plenum jacket
- Standard spool size 1000 feet

Rating:

- UL or C(UL)⁺ listed NEC Type CMP
- Constructed in accordance with UL Standard 444
- Complies with UL 910 Test modified ASTM Steiner Tunnel Test
- Temperature Range: 0° C to 60° C dry locations

Applications:

Indoor (non-conduit per NEC) within ducts, plenums and other spaces used for environmental air for:

- Intercom Systems
- Security Systems
- Sound and Audio
- Background Music
- Applications as defined in Article 800 Communications Circuits

Color Code:

Conductors: Black, Red

Jacket: Gray

Special Notes:

⁺C(UL) CMP Canadian UL accepted mark replaces PCC-FT6

Installation Precautions:

- Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.
- Due to the nature of PVC compounds to become non-pliable when stored or handled in ambient temperatures of 32° F or less, we recommend the following:

"Prior to installation, condition the cable for at least 24 hours at room temperature to provide the best flex properties for ease of installation".



Mechanical Characteristics

Number of Pairs	1
AWG Size	22
Stranding	Solid
Nom. Insulation Thickness	.010 (.25 mm)
Shield Type % Coverage	100% Aluminum Polyester Tape
Nom. Jacket Thickness	.015 (.38 mm)
Nom. O.D.	.121 (3.07 mm)
Drain Wire Size	22 AWG Solid

Electrical Characteristics Nominal

Capacitance @ 1 KHZ	54 pf/ft*
	177 pf/m*
	97 pf/ft**
	318 pf/m**
Conductor DCR (Resistance) @ 20° C	17.5 Ω per 1000 ft.

*Nominal Capacitance between conductors.

NOTE: Capacitance of unshielded cable may vary depending on installation environment

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.