

Plenecon II® Extra Flexible Plenum Fire Alarm Cable Unshielded

Description:

- ASTM bare copper
- Polymer alloy insulation
- Two conductors twisted to form a pair (six twists per foot)
- Unshielded cable construction
- Flexible plenum jacket
- Standard spool size 1000 feet

Rating:

- UL listed NEC type FPLP
- Constructed in accordance with UL Standard 1424
- Complies with UL 910 test modified ASTM Steiner Tunnel Test
- Temperature range: 0° C to 60° C dry locations

Applications

Indoor (non—conduit per NEC) within ducts, plenums and other spaces used for environmental air for:

- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

Color Code:


Conductors: 1. Black, 2. Red

Jacket: Red

Installation Precautions:

- Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.
- Due to the nature of PVC compounds to become non—pliable when stored or handled in ambient temperatures of 32° F or less, we recommend the following:

"Prior to installation, condition the cable for at least 24 hours at room temperature to provide the best flex properties for ease of installation".



Mechanical Characteristics

Number of Pairs	1
AWG Size	16
Stranding	Solid
Nom. Insulation Thickness	.010 (.25 mm)
Nom. Jacket Thickness	.015 (.38 mm)
Nom. O.D.	.161 (4.09 mm)

Electrical Characteristics Nominal

Capacitance @ 1 KHZ	32 pf/ft*
	105 pf/M*
Conductor D.C.R. (Resistance) @ 20° C	4.1 Ω per 1000 feet

*Nominal capacitance between conductors

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.