

RG-59/U Type CCTV Coaxial Cable

Description:

- ASTM bare copper conductor
- Foam polyethylene insulation
- Bare copper braid shield
- PVC jacket
- Standard spool size 1000 feet



Rating as per NEC:

- UL listed NEC type CM as defined in Article 800
- C(UL)⁺ listed CMH
- Constructed in accordance with UL Standard 444
- Listed as being resistant to the spread of fire as defined in Section 725 – 51 (c) of the National Electric Code. UL 1581 Vertical Tray Flame Test.

Applications

Indoor (non – conduit per NEC) for:

- CCTV

Jacket Color: Black

Special Notes:

⁺C(UL) CMH Canadian UL accepted mark replaces PCC – FT1

Construction	
Conductors	1
AWG Size	20
Stranding	Solid
Insulation with Tape Barrier	Foam Polyethylene
Insulation Nom. O.D.	.142 inch (3.61 mm)
Shield Type and % Coverage	Bare Copper Braid 95%
Jacket Type	PVC
Nom. O.D.	.232 inch (5.89 mm)

Coaxial Cable Loss Factors		
Nominal Attenuation		
Mhz	db/100 ft	db/100 m
1	.5	1.6
5	.7	2.3
10	.9	3.0
50	1.7	5.6
100	2.2	7.2
400	5.6	18.4
750	10	32.8
1000	9.1	29.8

Electrical Characteristics	
(Calculated Quantities)	
Nominal Capacitance Conductor to Shield	16.2 pf per foot
	56 pf per meter
Vel. of Prop.	82%
Nom. Imp.	75 Ω
Nom. D.C.R. (Resistance) @ 20° C	10.1 Ω per 1000 feet

Suggested Cambridge Connectors			
3 Piece (BNC)	2 Piece (BNC)	1 Piece (Twist-On)	"F Type" (1 Piece)
CN-BM53-2	CN-BM52-2	CN-BM51-2	CN-F59ALM

CAUTION: Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.