

Fire Protective Signaling Cable Unshielded

Description:

- ASTM bare copper
- Overall 105° C PVC insulation and jacket
- Two conductor parallel unshielded cable
- Polyester binders as required
- Standard spool size 1000 feet

Rating:

- UL listed NEC type FPL
- Constructed in accordance with UL Standard 1424
- Complies with UL 1581 Vertical Tray Flame Test
- Temperature range: -20° C to 105° C dry locations
- Meets 300 volt requirement as specified in Section 760-51 (c) of the NEC

Applications

Indoor (non-conduit per NEC) for:

- Power-Limited Fire Protective Circuits

Color Code:

Conductors: White, Red, Black



Mechanical Characteristics	
Number of Conductors	2
AWG Size	14
Stranding	Solid
Nom. Insulation Thickness	.032 (.81 mm)
Nom. O.D.	.128 x .250 (3.25 x 6.35 mm)
Nominal D.C.R. (Resistance) @ 20° C	2.6 Ω per 1000 feet

CAUTION: Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.