

Cluster Speaker Cable

Description:

- Multi Conductor Tray Cable Series
- PVC Insulation with Nylon
- Twisted Pair Construction
- 90° C PVC Sunlight Resistant Jacket
- Standard Spool Size 1000 Feet

Rating as per 1990 NEC:

- UL Listed NEC Type TC as defined in Article 340
- Constructed in accordance with UL Standard 1277
- Complies with UL 1581 Vertical Tray Flame Test
- Temperature range: -25° C to 90° C Dry Locations, 75° C Wet Locations
- Class 1 600 Volt
- Approved for Direct Burial and Outdoor Use

Applications:

Tray Cable in accordance with Article 340 and other applicable parts of the NEC for:

- Industrial Signaling and Control Circuits
- For use in Class 1 circuits as defined in Article 725
- Other applications as defined in NEC Article 340
- Cluster Speaker Cable

Color Code:

Conductors: 1. Black, 2. White

Jacket: Gray

Mechanical Characteristics	
Number of Pairs	1
AWG Size	10
Stranding	65 x 28
Nom. Insulation Thickness (PVC)	.020 inch (.51 mm)
Nom. Insulation Thickness (Nylon)	.005 inch (.13 mm)
Nom. Jacket Thickness	.047 inch (1.19 mm)
Nom. O.D.	.357 inch (9.07 mm)

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.