

Addressable System Fire Alarm Cables Unshielded

Description:

- ASTM bare copper
- Copolene II® insulation
- Short overall twist lengths (six twists per foot)
- Polyester binders as required
- Overall 75° C PVC jacket
- Standard spool size 1000 feet

Rating:

- UL listed NEC type FPL
- Constructed in accordance with UL Standard 1424
- Complies with UL 1581 Vertical Tray Flame Test
- Temperature range: -20° C to 75° C dry locations
- Meets 300 volt requirement as specified in Section 760-51 (c) of the NEC

Applications

Indoor (non-conduit per NEC) Data Grade Fire Alarm Cable for:

- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

Color Code:

Conductors: 1. Black, 2. Red
Jacket: Red



Mechanical Characteristics	
Number of Pairs	1
AWG Size	16
Stranding	Solid
Nom. Insulation Thickness	.015 (.38 mm)
Nom. Jacket Thickness	.030 (.76 mm)
Nom. O.D.	.223 (5.66 mm)

Electrical Characteristics Nominal	
Capacitance @ 1 KHZ	18 pf/ft.*
	59 pf/M*
Inductance @ 1 KHZ	.174 uh /ft.
Conductor D.C.R. (Resistance) @ 20° C	4.1 Ω per 1000 feet

*Nominal capacitance between conductors.

CAUTION: Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.