

## Sound and Audio Cable

### Description:

- Multiple conductor unshielded
- ASTM bare copper
- PVC insulation
- Twisted pair
- Overall 75° PVC jacket

### Rating as per NEC:

- UL listed NEC Type CL2
- Constructed in accordance with UL Standard 13
- Complies with UL 1581 Vertical Tray Flame Test
- Temperature range: -20° C to 75° C dry locations
- Meets 300 volt requirements as specified in section 800-51 of the NEC

### Applications:


Indoor (non-conduit per NEC) for:

- Home Entertainment Systems
- Sound and Audio
- Background Music
- Power-Limited Control Circuits

### Color Code:

**Conductors:** 1. Black, 2. Red

**Jacket:** Blue



Construction	
Number of Pairs	1
AWG Size	16
Stranding	(26x30)
Nom. Insulation Thickness	.010 inch (.25 mm)
Nom. Jacket Thickness	.020 PVC (.51 mm)
Nominal O.D.	.199 (5.05 mm)
Nom. D.C. R. Resistance @ 20°	4.2 Ω per 1000 Feet

**CAUTION:** Dry locations only. The electronic characteristics of this cable may change due to excessive tension, crushing, and application of pulling compounds during installation.

This document is the property of WEST PENN WIRE/CDT. The information contained herein is considered proprietary and not to be reproduced by any means without written consent of WEST PENN WIRE/CDT.