

MODEL NUMBER	PERFORMANCE						ELECTRICAL REQUIREMENTS						FEATURES						CABINET SIZE (IN.)			WINDOW OPENING (IN.)		WEIGHT				
	Cooling Area	BTUH Cooling	BTUH Heating	E.E.R.	Pints Per Hour	Room Air Delivery (CFM Max.)	Voltage	Amps Cooling	Amps Heating	Watts Cooling	Watts Heating	Plug Cap. Amps	Plug Type	Air Exchanger	Air Direction	Fan Speed	Adjustable Thermostat	Window Mount Type	Slide-Out Chassis	Slide-Out Filter	Additional Features	Width	Depth*	Height	Width (Min/Max)	Height (Min)	Net/Ship Weight (lbs)	
X CHASSIS	M3X05F2A	150	5000	-	9.7	1.4	160	115	5.0	-	515	-	125/15	A	-	2 Way	2	✓	Flex	-	✓	-	18 ⁵ / ₈	15 ¹ / ₈	12 ¹ / ₄	19 / 36	12 ³ / ₄	47 / 52
	M6X05F2A	150	5000	-	9.7	1.4	160	115	5.0	-	515	-	125/15	A	-	2 Way	2	✓	Flex	-	✓	EL	18 ⁵ / ₈	15 ¹ / ₈	12 ¹ / ₄	19 / 36	12 ³ / ₄	47 / 52
	M7X05F2A	160	5200	-	10.7	1.4	160	115	5.0	-	485	-	125/15	A	-	2 Way	2	✓	Flex	-	✓	EL/★	18 ⁵ / ₈	15 ¹ / ₈	12 ¹ / ₄	19 / 36	12 ³ / ₄	47 / 52
	M3X06F2A	200	6000	-	9.7	1.4	180	115	5.6	-	618	-	125/15	A	-	2 Way	2	✓	Flex	-	✓	-	18 ⁵ / ₈	15 ¹ / ₈	12 ¹ / ₄	19 / 36	12 ³ / ₄	49 / 54
	M6X06F2A	200	6000	-	9.7	1.4	180	115	5.6	-	618	-	125/15	A	-	2 Way	2	✓	Flex	-	✓	EL	18 ⁵ / ₈	15 ¹ / ₈	12 ¹ / ₄	19 / 36	12 ³ / ₄	49 / 54
Q CHASSIS	M7Q06F2A	200	6000	-	10.7	1.4	260	115	5.6	-	560	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL/★	20	18	12 ¹ / ₂	20 ³ / ₄ / 39	13	64 / 71
	M3Q08F2A	340	8000	-	9.8	2.6	260	115	7.5	-	815	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	-	20	18	12 ¹ / ₂	20 ³ / ₄ / 39	13	64 / 71
	M6Q08F2A	340	8000	-	9.8	2.6	260	115	7.5	-	815	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL	20	18	12 ¹ / ₂	20 ³ / ₄ / 39	13	73 / 79
	M7Q08F2A	340	8000	-	10.8	2.0	260	115	7.0	-	745	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL/★	20	19 ⁷ / ₈	12 ¹ / ₂	20 ³ / ₄ / 39	13	73 / 79
	MEQ07F2A	300	7000	4000	9.7	2.4	200	115	7.5	12.0	720	1380	125/15	A	-	4 Way	2	✓	Flex	-	✓	HC	20	19 ⁷ / ₈	12 ¹ / ₂	20 ³ / ₄ / 39	13	73 / 79
	M3Q10F2A	450	10000	-	9.8	3.3	260	115	9.0	-	1020	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	-	20	19 ⁷ / ₈	12 ¹ / ₂	20 ³ / ₄ / 39	13	73 / 79
M6Q10F2A	450	10000	-	9.8	3.3	260	115	9.0	-	1020	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL	20	19 ⁷ / ₈	12 ¹ / ₂	20 ³ / ₄ / 39	13	74 / 80	
T CHASSIS	M3T12F2A	550	12000	-	9.8	4.1	340	115	11.0	-	1225	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	-	23 ³ / ₄	23 ³ / ₄	15 ³ / ₈	24 / 39	16 ¹ / ₄	97 / 104
	M6T12F2A	550	12000	-	9.8	4.1	340	115	11.0	-	1225	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL	23 ³ / ₄	23 ³ / ₄	15 ³ / ₈	24 / 39	16 ¹ / ₄	97 / 104
	M7T12F2A	550	12000	-	10.8	3.9	310	115	10.5	-	1110	-	125/15	A	✓	4 Way	3	✓	Flex	-	✓	EL/★	23 ³ / ₄	23 ³ / ₄	15 ³ / ₈	24 / 39	16 ¹ / ₄	97 / 104
J	MEJ12E7A	550	12000 11500	10200 8700	9.8	4.3	340	230 208	5.6 6.2	13.4 12.3	1225 1175	3180 2870	250/20	C	✓	4 Way	2	✓	Rigid	✓	✓	HC	24 ³ / ₄	23 ¹ / ₂	16 ³ / ₈	24 ³ / ₄ / 39	16 ³ / ₈	107 / 112
D CHASSIS	M7D16E2A	850	16000	-	10.7	5.0	525	115	12.0	-	1495	-	125/15	A	✓	4 Way	3	✓	Rigid	✓	✓	EL/★	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	125 / 130
	M6D18E7A	1000	18000	-	9.8	5.5	525	230 208	8.5	-	1836	-	250/15	B	✓	4 Way	3	✓	Rigid	✓	✓	EL	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	125 / 130
	M7D18E7A	1000	18000	-	10.7	6.0	525	230 208	7.6	-	1680	-	250/15	B	✓	4 Way	3	✓	Rigid	✓	✓	EL/★	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	125 / 130
	MED18E7A	1000	18000 17500	10200 8300	9.8	5.5	525	230 208	7.9 8.5	15.0 13.5	1836 1785	3320 2690	250/20	C	✓	4 Way	2	✓	Rigid	✓	✓	HC	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	125 / 130
	M6D24E7A	1400	24000	-	8.5	8.5	575	230 208	13.5 14.4	-	2830 2765	-	250/20	C	✓	4 Way	3	✓	Rigid	✓	✓	EL	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	155 / 160
	MED24E7A	1400	24000 23500	16000 13400	8.5	8.2	550	230 208	13.5 14.4	22.8 20.9	2830 2765	5200 4280	250/30	D	✓	4 Way	2	✓	Rigid	✓	✓	HC	26 ¹ / ₂	25 ³ / ₈	17 ¹ / ₄	26 ³ / ₄ / 40	18 ⁵ / ₈	155 / 160
V	M3V10S2A	450	10000	-	9.5	3.1	300	115	10.0	-	1050	-	125/15	A	✓	4 Way	3	✓	Slider	-	-	-	14 ¹ / ₂	24 ¹ / ₄	20 ¹ / ₂	15 ¹ / ₂ min	21	100 / 106
PORT	SMPEB08F2A	300	7500	-	7.5	1.75	170	115	7.5	-	800	-	125/15	A	-	2 Way	2	✓	Port.	N/A	✓	-	17	17	33	N/A / N/A	78	84



MODELS AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

Models designated 230/208 Volts are designed to operate at a minimum of 197 Volts.

HC - 2 Speed Cooling, 2 Speed Heating. **EL** - Electronic touch control with remote.

★ - ENERGY STAR® qualified model. *Cabinet Depth includes decorative front.