



Assembly Instructions

To avoid the possibility of damaging the Clean Park[®],
the garage floor must be clean and smooth.

1. Clean the garage floor by sweeping and/or vacuuming the area where the Clean Park[®] will be placed. All debris must be removed. Any cracks in the floor must either be repaired or covered with duct tape to leave a smooth surface that will not cut into the Clean Park[®].
2. Lay out the Clean Park[®] with the name facing up.
3. Attach the side pieces onto the long sides of the Clean Park[®]:
 - a. Locate the **long** V-shaped side pieces. Start at one of the corners closest to the garage door. Slip the a long side piece onto the vinyl sheeting until it touches the V-shaped corner in the side piece. Align the edge of the vinyl sheeting that is closest to the garage door, flush with the edge of the side piece. **See figure 1.** Next, press on the top of the side piece, using your hand or **your foot (much easier than using your hand)**, until it snaps down and locks in place.



Figure 1

- b. Slip another long side piece onto the vinyl sheeting until the vinyl sheeting touches the V-shaped corner in the side piece. Slide the side piece onto the vinyl sheeting **until it touches** the previously installed side piece. Next, press on the top of the side piece until it snaps down and locks in place. Repeat this step until you have snapped side pieces down the entire length of the vinyl sheeting. You should have 1½" of vinyl sheeting protruding beyond the last side piece at the back of the garage (opposite side of the garage door). **See figure 2.** If you have more than 1½", use a scissors and trim off the excess vinyl sheeting.




Figure 2

c. Repeat steps 3a. and 3b. along the opposite side of the vinyl sheeting.

4. Attach the side pieces onto the back side (opposite of the garage door) of the Clean Park®:

a. Locate the **short** V-shaped side pieces. Starting at one of the corners, slip the edge piece onto the vinyl sheeting so that it touches the V-shaped corner in the side piece. Slide the side piece towards the corner until the tops of both side pieces are about 1/4" apart. **See figure 3.** Next, press on the top of the side piece until it snaps down and locks in place.




Figure 3

b. Slide another short side piece onto the vinyl sheeting until the vinyl sheeting touches the V-shaped corner in the side piece. Slide the side piece onto the vinyl sheeting until it touches the previously installed side piece. Next, press on the top of the side piece until it snaps down and locks in place.

c. Repeat this step until you have snapped the remaining side pieces in place.

5. Attach the front ramp onto the Clean Park®:

a. Locate the piece that is flat on one side with a round tube on the other side. Position it underneath the vinyl sheeting on the left side of the Clean Park®. **See figure 4.**



Figure 4

Overlap the flat side of the bottom piece with the flat side of the side piece. Locate the two top pieces, each having one **rounded corner**. Position the top piece so that the rounded corner will be

positioned on top of the vinyl sheeting along the side edge. **See figure 5.**




Figure 5

Next, align the top and bottom pieces and press the top down onto the bottom piece, until the two pieces snap together. Do not use the other top piece with the rounded corner until step 5d.

b. Align another bottom piece under the vinyl sheeting so that it touches the previously assembled bottom piece. Snap another top piece onto the bottom piece.

c. Repeat step 5b. until all of the segments, except the last segment, are assembled.

d. Repeat step 5a to complete the last segment.

Warning:

Rocks and other sharp objects may puncture the Clean Park®. To avoid punctures, regularly remove debris by sweeping with a soft bristle broom.

Discoloration of the vinyl sheeting may occur over time and does not affect the integrity of the material. Tire imprints due to the weight of your vehicle on the vinyl sheeting may occur and will not affect your Clean Park®.

Cleaning Instructions:

Remove one or more of the end pieces closest to the garage door. Be careful not to puncture or cut the vinyl sheeting with the edge of the top piece as you pull it off. Sweep the Clean Park® with a soft bristle broom. Hose off the Clean Park®. Use a soft bristle broom to push water towards the open area, off of the Clean Park®. Only a mild dish soap may be used on the Clean Park®. **Do Not Use Solvents, Harsh Chemicals, Abrasive Cleaners or Bleach.**

U.S. Patent # 6,258,430

Warning:

The Clean Park® is Slippery When Wet.

Do Not Use Snow Chains or Studded Snow Tires on the Clean Park® without taking special precautions to protect the vinyl sheeting. Call for details.

Do Not Turn Front Tires While Vehicle is Stationary on the Clean Park®.