

Features

Coffee brewers with portable servers

- Brews 16.3 to 18.9 gallons of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon batches.
- Patented server heat control automatically shuts off once target temperature is reached. Can be set to 175°-190°F.
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Remote 1 or 2 server docking stations for additional satellite coffee serving.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.
- Variable batch selector knob lets you brew large batches or small servings.
- International electrical configurations available.

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-11-TL

Product No. : 30344.1001

Dimensions:

15⁷/₈" H x 3⁵/₈" W x 4¹⁷/₃₂" D

40.32 cm H x 9.21 cm W x 11.51 cm D

Easy Clear® ED-11-TL

Product No. : 30244.1001

Dimensions:

14³/₁₆" H x 5¹/₁₆" W x 5¹/₁₆" D

31.0 cm H x 12.86 cm W x 12.86 cm D

Single/Dual Filter Pack

Product No. : 20100.0000

Packed per case: 500

Dimensions: 5¹/₄" Base x 3³/₄" Sidewall

10.8 cm Base x 9.52 cm Sidewall



SH Server

Product No. : 27850.0001

Two Position Drip Tray

Product No. : 27150.0000



*Model Dual SH with
1.5 gallon SH Servers*
(servers sold separately)*

Dimensions: 35.8" H x 18" W x 22.2"D

* International models may vary in appearance.



1.5 gallon SH Servers on 2SH Stand
with dual drip tray (optional)

ITEM#

PROJECT

DATE

**International
Model**

Dual SH

Model

Dual SH

BUNN®

Corporate Offices

1400 Stevenson Drive
Springfield, Illinois 62703

Phone

800-637-8606

217-529-6601

Fax

217-529-6644

Technical Services

800-286-6070

Internet

<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone

562-926-0764

Fax

562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone

905-841-2866

Fax

905-841-2775

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
Dual SH Brewer	27900.0001	120/208	28.9	2 @ 2850	5900	16.3 gal./hr.	13	90 lbs. (40.9 kg)	No
Dual SH Brewer†	27900.0008	120/208	28.9	2 @ 2850	5900	16.3 gal./hr.	13	91 lbs. (41.3 kg)	No
Dual SH Brewer	27900.0002	120/240	29.1	2 @ 3300	6800	18.9 gal./hr.	13	91 lbs. (41.3 kg)	No
Dual SH Brewer*	27900.0020	120/240	29.1	2 @ 3300	6800	18.9 gal./hr.	13	91 lbs. (41.3 kg)	No
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1½ gal.	2.2	17 lbs. (7.7 kg)	No
SH Server(1.75 gal.)	27850.0002	n/a	n/a	n/a	n/a	1¾ gal.	2.2	18 lbs. (8.2 kg)	No
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1½ gal.	2.2	18 lbs. (8.2 kg)	No
1SH Stand	27825.0000	120	.8	n/a	90	Holds 1 SH Server	1.7	13 lbs. (5.9 kg)	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes

†Model has recovery booster. *Models have black decor.

Note: Soft Heat® Brewers and Servers are boxed and shipped separately. All brewers have mechanical thermostats.

Electrical: Brewer is 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60Hz.

Plumbing: 20-90 psi (69-621 kPa). Machine supplied with ¼" (6.4 mm) male fitting.

