

Features

10 Gallon Hot Water Machine

- Dispenses up to 24 gallons of boiling water per hour for food prep and cleaning.
- Precise temperature (212°F) ensures consistent, high quality results.
- Ideal for prep of large amounts of mashed potatoes, gravy, cheese sauce, gelatin, oatmeal, & many more foods.
- Includes dry-plug prevention for easy installation.
- International electrical configurations available.



Model H10X

Dimensions: 34.5"H x 10.3"W x 24.5"D

ITEM#

PROJECT

DATE

Model

H10X

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems to assure perfect taste.

Easy Clear® EQ-11-TL
Product No. : 30344.1001
Dimensions:
15⁷/₈" H x 3³/₈" W x 4¹⁷/₃₂" D



Easy Clear® ED-11-TL
Product No. : 30244.1001
Dimensions:
14³/₁₆" H x 5¹/₁₆" W x 5¹/₁₆" D

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	°F Settings	Gal./Hr. cold water input 35°	Gal./Hr. hot water input 140°	Cu. Ft.	Shipping Weight	Cord Attached
H10X	26300.0001	208	38.58	2 @ 4000	8025	212	13.2	24.8	8.6	67 lbs. (30.4 kg)	No
H10X	26300.0000	240	33.44	2 @ 4000	8025	212	13.2	24.8	8.6	67 lbs. (30.4 kg)	No

Electrical: 208 volt or 240 volt (depending on model) 2 wires plus ground service, single phase. Supplied strain relief on back of machine.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" (6.3 mm) OD male flare fitting.

