

### Features

#### 2 Gallon Hot Water Machine

- Two gallons of hot water in a space-saving machine just 7" wide to fit any counter.
- Fresh, hot water is always available since the HW2 is hooked to your water line.
- High quality, easy-to-clean stainless steel exterior and tank for a long, dependable life.
- Includes drip tray.
- International electrical configurations available.



*Model HW2\**

Dimensions: 24"H x 7.3"W x 14.3"D

*\* International models may vary in appearance.*

### Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems to assure perfect taste.

**Easy Clear® EQ-17-TL**  
Product No. : 30200.1000  
Dimensions:  
12<sup>7</sup>/<sub>16</sub>" H x 2<sup>1</sup>/<sub>2</sub>" W x 3" D



**Easy Clear® ED-17-TL**  
Product No. : 30201.1001  
Dimensions: 8<sup>1</sup>/<sub>4</sub>" x 2<sup>5</sup>/<sub>16</sub>" Dia.

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

**International Model**

*HW2A*

**Model**

*HW2*

## BUNN®

**Corporate Offices**  
1400 Stevenson Drive  
Springfield, Illinois 62703  
**Phone**  
800-637-8606  
217-529-6601  
**Fax**  
217-529-6644  
**Technical Services**  
800-286-6070  
**Internet**  
<http://www.bunnomatic.com>

**Western Regional Office**  
16431 Carmenita Road,  
Cerritos, California 90701  
**Phone**  
562-926-0764  
**Fax**  
562-926-0858

**Canadian Office**  
280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9  
**Phone**  
905-841-2866  
**Fax**  
905-841-2775

Patents Apply



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	°F Settings	Dispensing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
HW2	02500.0001	120	14.71	1700	1765	200	3 gal./hr.	2.3	22 lbs. (10.0 kg)	Yes

Electrical: Model requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Plumbing: 20-90 psi (69-621 kPa). Supplied with 1/4" (6.3 mm) OD male flare fitting.

