

Features

12 Cup Automatic Coffee Brewer

- Brews 6.8 gallons of perfect coffee per hour.
- Five separately controlled warmers.
- All stainless steel construction.
- Can also be operated as a pourover unit.
- Faucet kit available.
- SplashGard® funnel deflects hot liquids away from the hand.
- UL listed. NSF approved.



Model RL 35

(5 warmers)

(decanters not included)

Dimensions: 23.5" H x 24" W x 18.3" D

ITEM#

PROJECT

DATE

Model

RL 35

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL
Product No. : 30200.1000
Dimensions:
12⁷/₁₆" H x 2¹/₂" W x 3" D



Easy Clear® ED-17-TL
Product No. : 30201.1001
Dimensions: 8¹/₄" H x 2³/₁₆" Dia.

Paper Filter Pack
Product No. : 20115.0000
Packed per case: 1,000
Dimensions: 4¹/₄" Base x 2³/₄" Sidewall



Easy Pour® black decanter
Product No. : 06100.0101
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)

Easy Pour® orange decanter (for decaf)
Product No. : 06101.0101
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
RL	20825.0000	120/240	19.2	3500	4050	6.8 gal./hr.	9.3	44 lbs. (20.0 kg)	No

Electrical: Model requires 3-wires plus ground service rated 120/240V (115/230, 120/208), single phase, 60 hz.

Plumbing: 10-90 psi (69-621 kPa). Supplied with ¼" OD male flare fitting.

