

Features

12 Cup Automatic Coffee Brewer

- Brews 6.8 gallons of perfect coffee per hour.
- Five separately controlled warmers.
- All stainless steel construction.
- Models available with faucet. Faucet kits available for existing models also.
- SplashGard® funnel deflects hot liquids away from the hand.
- UL listed. NSF approved.



Model RT 35

(5 warmers)

(decanters not included)

Dimensions: 21.2" H x 24" W x 18.3" D

ITEM#

PROJECT

DATE

Model

RT 35
RTF 35

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL
Product No. : 30200.1000
Dimensions:
12⁷/₁₆" H x 2¹/₂" W x 3" D



Easy Clear® ED-17-TL
Product No. : 30201.1001
Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

Paper Filter Pack
Product No. : 20115.0000
Packed per case: 1,000
Dimensions: 4¹/₄" Base x 2³/₄" Sidewall



Easy Pour® black decanter

Product No. : 06100.0101

Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No. : 12487.0001*

RWS1 Product No. : 12203.0010

*Also available with side handles or black decor.



BUNN®

Corporate Offices

1400 Stevenson Drive
Springfield, Illinois 62703

Phone
800-637-8606
217-529-6601

Fax
217-529-6644

Technical Services
800-286-6070

Internet
<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone
562-926-0764

Fax
562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone
905-841-2866

Fax
905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
RT	20835.0000	120/240	19.2	3500	4050	6.8 gal./hr.	9.4	42 lbs. (19.1 kg)	No
RTF (w/faucet)	20835.0004	120/240	19.2	3500	4050	6.8 gal./hr.	9.4	46 lbs. (20.9 kg)	No

Electrical: Model requires 3-wires plus ground service rated 120/240V (115/230, 120/208), single phase, 60 hz.

Plumbing: 20-90 psi (132-621 kPa). Machine supplied with 1/4" OD male flare fitting.

