

# BUNN® Single Brewer with Portable Server

## Features

### Single Coffee Brewer

- Brews 5.1 to 11.4 gallons of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon batches.
- Adjustable bypass ensures perfect coffee regardless of batch size.
- Hot water faucet does not affect brew level.
- Electronic timer insures fast set up and accurate brew levels.
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- 1.5GPR portable server (included) has a patented Safety-Fresh® brew-through lid with vapor seal and spill protection.
- SplashGard® funnel deflects hot liquids away from the hand.
- International electrical configurations available.



*Model Single®  
with 1.5GPR server\**

Dimensions: 29.3" H x 9.25" W x 22.2" D

\* International models may vary in appearance.

## Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

### Easy Clear® EQ-11-TL

Product No. : 30344.1001

Dimensions:

15⅞" H x 3⅝" W x 4⅙" D

40.32 cm H x 9.21 cm W x 11.51 cm D

### Easy Clear® ED-11-TL

Product No. : 30244.1001

Dimensions:

14⅜" H x 5⅙" W x 5⅙" D

31.0 cm H x 12.86 cm W x 12.86 cm D



### Single/Dual Filter Pack

Product No. : 20100.0000

Packed per case: 500

Dimensions: 5¼" Base x 3¾" Sidewall

10.8 cm Base x 9.52 cm Sidewall



1.5GPR Safety-Fresh® portable server with bail handles & RWS1 warming stand.

### 1.5GPR

Product No. : 20950.0002

Dimensions:

10¼" H x 6¾" W x 12⅝" D

26.0 cm H x 17.2 cm W x 32.1 cm D

Depth=10¼" w/o guard

26.0 cm w/o guard

Depth=12⅜" with guard

32.38 cm w/ guard

Width=7¾" without handle

19.68 cm w/o handle

Width=7⅝" with handle

19.37 cm w/ handle



RWS1 Product No. :

12203.0010

Dimensions: 7.5" H x 8¼" W x 9⅙" D

19.05 cm H x 20.96 cm W x 23.62 cm D

ITEM#

PROJECT

DATE

**International Model**

*Single*

**Model**

*Single*

## BUNN®

### Corporate Offices

1400 Stevenson Drive  
Springfield, Illinois 62703

**Phone**

800-637-8606

217-529-6601

**Fax**

217-529-6644

**Technical Services**

800-286-6070

**Internet**

<http://www.bunnomatic.com>

### Western Regional Office

16431 Carmenita Road,  
Cerritos, California 90701

**Phone**

562-926-0764

**Fax**

562-926-0858

### Canadian Office

280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9

**Phone**

905-841-2866

**Fax**

905-841-2775

Patents  
Apply



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Thermostat	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
Single <sup>†</sup> *	23050.0006	120	16.3	1800	1950	Mechanical	5.1 gal./hr.	7.0	57 lbs. (25.9 kg)	No
Single <sup>**</sup>	23050.0007	120	18.3	1800	2200	Mechanical	5.1 gal./hr.	7.1	58 lbs. (26.3 kg)	No
Single <sup>**</sup>	23050.0010	120/208	19.5	3700	4050	Mechanical	10.6 gal./hr.	7.0	58 lbs. (26.3 kg)	No
Single <sup>**</sup>	23050.0011	120/240	18.3	4000	4400	Mechanical	11.4 gal./hr.	7.0	59 lbs. (26.8 kg)	No

All include Safety-Fresh® server with additional orange faucet handle and decal for decaf service.

<sup>†</sup> Model 23050.0006 has a plastic funnel. The other models listed include a stainless steel funnel.

\* One setting. \*\* Three settings.

Electrical: 120V models require 2-wires plus ground service rated 120V, single phase, 60 Hz.

120/208V or 120/240V models require 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (69-621 kPa). Supplied with 1/4" (6.4 mm) male flare fittings.

