

Features

BrewWISE® Brewing System with ThermoFresh Servers

- Three batch size capability.
- Stores individual coffee recipes so operator can easily brew many different varieties.
- Coffee extraction controlled with pre-infusion and Pulse-Brew™, digital temperature control, and large sprayhead; coffee strength controlled with variable by-pass
- Operate any combination of equipment error-free with wireless brewer-grinder interface through the Smart Funnel
- SplashGard® funnel and optional funnel locks help improve safety.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Black and Stainless models available
- ThermoFresh® servers are vacuum insulated to keep coffee hot and fresh for hours
- Create coffee recipe cards with custom recipes, ad cards with messages that display on the brewer LCD, and dedicated funnels for special coffees with the BrewWISE Recipe Writer (#34444.0000) on your PC (Windows compatible).



*Model Dual TF DBC with
1.5 gallon TF Servers
(servers sold separately)*

Dimensions: 35.7" H x 21.8" W x 20.2" D

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-11-TL
Product No. : 30344.1001
Dimensions:
15⁷/₈" H x 3⁵/₈" W x 4¹⁷/₃₂" D



Easy Clear® ED-11-TL
Product No. : 30244.1001
Dimensions:
14³/₁₆" H x 5¹/₁₆" W x 5¹/₁₆" D

Single/Dual Filter Pack
Product No. : 20100.0000
Packed per case: 500
Dimensions: 5¹/₄" Base x 4¹/₄" Sidewall



BrewWISE Recipe Writer (BRW)

Product No.: 34444.0000
Dimensions:
2³/₁₆" H x 6³/₈" W x 9¹/₂" D



Recipe Card - Program a recipe to be used on brewer or grinder.
Product No.: 34447.0000

Ad Card - Program a message to appear on the brewer's display.
Product No.: 34448.0000

G9-2T DBC

Product No.: 33700.0000
• Grinder holds 6 pounds each of regular and decaf or specialty beans.



BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

International Model

Dual TF DBC

Models

Dual TF DBC

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Funnel Locks	Cord Attached
Dual TF DBC	34600.0000	120/240	30	2@3300	6850	18.9 gal/hr	14	92.5 lbs.	Yes	No
Dual TF DBC*	34600.0001	120/240	30	2@3300	6850	18.9 gal/hr	14	92.5 lbs.	Yes	No
Dual TF DBC	34600.0002	120/240	30	2@3300	6850	18.9 gal/hr	14	92.5 lbs.	No	No
Dual TF DBC*	34600.0003	120/240	30	2@3300	6850	18.9 gal/hr	14	92.5 lbs.	No	No
Dual TF DBC	34600.0004	120/208	30	2@2850	5900	18.9 gal/hr	14	92.5 lbs.	No	No
Dual TF DBC*	34600.0005	120/208	30	2@2850	5900	18.9 gal/hr	14	92.5 lbs.	No	No
Dual TF DBC	34600.0006	120/208	30	2@2850	5900	18.9 gal/hr	14	92.5 lbs.	Yes	No
Dual TF DBC*	34600.0007	120/208	30	2@2850	5900	18.9 gal/hr	14	92.5 lbs.	Yes	No
G9-2T DBC	33700.0000	120	9.4	n/a	n/a	n/a	5.1	66.0 lbs.	n/a	Yes
G9-2T DBC*†	33700.0001	120	9.4	n/a	n/a	n/a	5.1	66.0 lbs.	n/a	Yes
TF Server	34850.0000	n/a	n/a	n/a	n/a	1.5 gallons	2.8	13.8 lbs.	n/a	No
TF Server*	34850.0001	n/a	n/a	n/a	n/a	1.5 gallons	2.8	13.8 lbs.	n/a	No

* Models have black decor. † Special order unit (call for availability).

Electrical: Brewer is 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60Hz.
Grinder is 2-wires plus ground service rated 120V, 60Hz, circuit required, ¼HP motor.

Plumbing: 20-90 psi (69-621 kPa). Machine supplied with ¼" (6.4 mm) male fitting.

