

AMPLIFIER SPECS CHART

Model Numbers	Output Power (/Channel)	Channels	Frequency Response*	Distortion**	Speaker Outputs	AC Line Draw***	Dimensions	Product Weight
BPA60	60W	1	50 Hz to 15 kHz	2% Max	8-ohm/25V, 16-ohm, 25VCT, 70V	180W	15-1/4" W x 3-1/2" H x 8-1/4" D	17 lb.
C10	10W	1	70 Hz to 16 kHz	1% Max	70V, 25V, 16-ohm, 8-ohm, 4-ohm	38W	11-3/8" W x 2-7/8" H x 7-3/8" D	5 lb.
C20						50W		6 lb.
C20MOH	20W							
C35	35W					85W		16 lb.
C60	60W	1	70 Hz to 16 kHz - Transformer; 20 Hz to 20 kHz - Direct	1% Max	70V, 25V, 16-ohm, 4-ohm direct	148W	14-1/2" W x 3-3/4" H x 11" D	18 lb.
C100	100W					220W		20 lb.
GA2	1.5W	1	200 Hz to 15 kHz	2% Max	8- & 600-ohm	4W	5-1/2" W x 4-1/8" H x 2-1/4" D	2 lb.
GA6A	6W	1	30 Hz to 12 kHz	2% Max	70V, 25V, 8-ohm	16W	8-1/2" W x 2-3/4" H x 6" D	5 lb.
GS35	35W					0.9A		17 lb.
GS60	60W	1	65 Hz to 20 kHz - Transformer; 20 Hz to 20 kHz - Direct	0.5% Max	70V, 25V, 25VCT, 8-ohm, 4-ohm direct	1.3A	16-1/2" W x 3-1/2" H x 13-1/2" D	20 lb.
GS100	100W					2.2A		23 lb.
GS150	150W					3.0A		29 lb.
GS250	250W					5.0A		30 lb.
HTA125A	125W							
HTA250A	250W	1	20 Hz to 20 kHz	0.5% Max	70V, 25VCT, 25V, 8-ohm, 4-ohm	520W		50 lb.
M300	300/600W	2 or 1	20 Hz to 20 kHz	0.5% Max	4- to 8-ohm (2 channel mode); 70V (1 channel mode)	12A	17" W x 3-1/2" H x 18-1/2" D (not including brackets)	41 lb.
M450	450/900W					15A		44 lb.
M600	600/1200W					20A		46 lb.
MT250D	250W	1	20 Hz to 20 kHz	2% Max	100V, 70V, 25V, 12.5V, 8-ohm	650W	19" W x 13" H x 5-1/4" D	57 lb.
PM3180	100W 60W 20W	3	70 Hz to 20 kHz - Trans (Amp 1 & 2); 70 Hz to 15 kHz - Trans (Amp 3); 20 Hz to 20 kHz - Direct (Amp 1 & 2); 20 Hz to 15 kHz - Direct (Amp 3)	0.5% - Amp 1&2; 1% - Amp 3 (Max)	70V, 25V, 8-ohm, 4-ohm direct	430W	17" W x 5-1/2" H x 12-1/2" D	38 lb.
TPU15A	15W	1	70 Hz to 12 kHz	2% Max	70V, 25V, 8-ohm	48W	11" W x 2-3/4" H x 2-3/8" D	4 lb.
TPU35B	35W		70 Hz to 15 kHz	1% Max	70V, 25V, 25VCT, 16-ohm	0.7A	14-1/4" W x 8-3/8" H x 3-5/8" D	13 lb.
TPU60B	60W					1.5A		15 lb.
TPU100B	100W					2A	18 lb.	
TPU250	250W					70V, 25V	5A	19" W x 10-1/2" H x 3-7/8" D
V35	35W	1	45 Hz to 20 kHz - Transformer; 20 Hz to 20 kHz - Direct	0.5% - Transformer; 0.1% - Direct (Max)	70V, 25V, 8-ohm, 4-ohm direct	0.6A	16-1/2" W x 3-1/2" H x 12" D	24 lb.
V60	60W					1.3A		28 lb.
V100	100W					2.0A		32 lb.
V150	150W					3.5A		35 lb.
V250	250W					5.5A		40 lb.
WV100	100W	1	45 Hz to 20 kHz - Transformer; 20 Hz to 20 kHz - Direct	0.5% - Transformer; 0.1% - Direct (Max)	70V, 25V, 8-ohm, 4-ohm direct	2.0A	14-1/8" W x 21" H	27 lb.
WV150	150W					3.5A		29 lb.
WV250	250W					5.5A		28 lb.
X300	300W	2	20 Hz to 20 kHz	0.5% Max	70V direct	12A	17" W x 3-1/2" H x 18-1/4" D (not including brackets)	41 lb.
X450	450W					15A		44 lb.
X600	600W					20A		46 lb.

* @ -2dB FRP Transformer output;
@ FRP for Direct outputs

** Bandwidth limited to frequency response

*** FRP @ 120V AC line voltage

Specifications subject to change without notice.