




# TENSIONED ADVANTAGE® DELUXE ELECTROL®

Automatic Electric Projection Screen Model

## SPECIFICATION DATA

DA-LITE SCREEN COMPANY, INC.  
3100 North Detroit Street  
Post Office Box 137  
Warsaw, Indiana 46581-0137  
Phone: 574-267-8101  
800-622-3737  
Fax: 574-267-7804  
Toll Free Fax: 877-325-4832  
www.da-lite.com  
e-mail: info@da-lite.com

**SUGGESTED SPECIFICATIONS:** \_\_\_\_\_ projection screen(s), \_\_\_\_\_(H) x \_\_\_\_\_ (W). The Tensioned Advantage® Deluxe screen shall have two motors, one to operate door and one to operate screen. Door motor electrically operated 120 volt (60 Hz) not more than 1.2 amp. Shall have motor mounted inside the roller, to be three wire with ground, quick reversal type, oiled for life, with automatic thermal overload cutout, integral gears, capacitor and an electric brake to prevent coasting. To have pre-set but adjustable limit switches to automatically stop fabric door in the "down" position. The door will lift to the closed position where a micro switch shall cut off the electrical current to the door motor. The roller to be of rigid aluminum. Screen motor is electrically operated 120 volt (60 Hz) not more than 2.4 amp. Shall have motor mounted inside the roller, to be three wire with ground quick reversal type, oiled for life, with automatic thermal overload cutout, integral gears, capacitor and an electric brake to prevent coasting. To have pre-set but adjustable limit switches to automatically stop picture surface in the "up" and "down" positions. The roller to be of rigid metal. Screen fabric to be seamless, flame retardant and mildew resistant vinyl, with black masking borders standard. Each side of the fabric to have tab guide cable system to maintain even lateral tension and hold surface flat. Custom slat bar with added weight maintains vertical tension on the screen surface. The ends of the slat to be protected by heavy duty plastic caps enclosing a preset adjustable mechanism for screen tensioning. Case shall be a white powder coated extruded aluminum. Bottom of case to be self-trimming with a built-in flange around the bottom of the case. A section of the bottom of the case shall be an aluminum door equipped with hinges so that it opens and closes automatically with the lowering and raising of the picture surface. The balance of the bottom of the case shall be a second hinged aluminum door with manual opening to provide access. Hinges shall be mounted in a concealed way. Junction box shall be internally integrated into the housing making it possible to install the housing and wire to the building's electrical system during construction. The junction box shall contain a quick connect connector that is mounted in the housing for easy plug-in connection to the motorized fabric and roller assembly. The motorized fabric and roller assembly to be installed in the case at the factory or at a later time at the job site. To be complete with three position control switch and cover plate. Suitable for use in environmental air space in accordance with section 300-22 (c) of the National Electric Code, and sections 2-128, 12-010 (3) and 12-100 of the Canadian Electrical Code, part 1, CSA C22.1. Screen to be listed by Underwriters' Laboratories.



### VIDEO (NTSC 4:3) FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case (does not include flange)		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	Lbs.	Kg
43" x 57"	109 x 145	72"	183	79 <sup>1</sup> / <sub>4</sub> "	201	102	46.3
50" x 67"	127 x 170	84"	213	90 <sup>1</sup> / <sub>4</sub> "	229	114	51.7
60" x 80"	152 x 203	100"	254	104 <sup>1</sup> / <sub>4</sub> "	265	125	56.7
69" x 92"	175 x 234	120"	305	118 <sup>1</sup> / <sub>4</sub> "	300	148	67.1
87" x 116"	221 x 295	150"	381	145 <sup>1</sup> / <sub>4</sub> "	369	170	77.1
108" x 144"	274 x 366	180"	457	170 <sup>1</sup> / <sub>4</sub> "	432	189	85.7
120" x 160"	305 x 406	200"	508	187 <sup>1</sup> / <sub>4</sub> "	476	203	92.1

### HDTV (16:9) FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case (does not include flange)		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	Lbs.	Kg
45" x 80"	114 x 203	92"	234	102 <sup>3</sup> / <sub>4</sub> "	261	125	56.7
52" x 92"	132 x 234	106"	269	115 <sup>1</sup> / <sub>4</sub> "	293	140	63.5
54" x 96"	137 x 244	110"	279	119 <sup>3</sup> / <sub>4</sub> "	304	145	65.8
58" x 104"	147 x 264	119"	302	128 <sup>1</sup> / <sub>4</sub> "	326	150	68.0
65" x 116"	165 x 295	133"	338	141 <sup>1</sup> / <sub>4</sub> "	359	163	73.9
78" x 139"	198 x 353	159"	404	166 <sup>1</sup> / <sub>4</sub> "	422	188	85.3
90" x 160"	229 x 406	184"	467	184	405	203	92.3

### 16:10 WIDE FORMAT DIMENSIONS

Viewing Area		Nominal Diagonal		Overall Length of Case (does not include flange)		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	Lbs.	Kg
50" x 80"	127 x 203	94"	239	103 <sup>3</sup> / <sub>4</sub> "	264	125	56.7
60" x 96"	152 x 244	113"	287	120 <sup>3</sup> / <sub>4</sub> "	307	145	65.8
69" x 110"	175 x 279	130"	330	134 <sup>3</sup> / <sub>4</sub> "	342	157	71.2
87" x 139"	221 x 353	164"	417	163 <sup>1</sup> / <sub>4</sub> "	415	188	85.3

### SQUARE FORMAT DIMENSIONS

Viewing Area		Overall Length of Case (does not include flange)		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	Lbs.	Kg
50" x 50"	127 x 127	73 <sup>1</sup> / <sub>4</sub> "	186	93	42.2
60" x 60"	152 x 152	84 <sup>1</sup> / <sub>4</sub> "	214	104	47.2
70" x 70"	178 x 178	95 <sup>3</sup> / <sub>4</sub> "	243	116	52.6
84" x 84"	213 x 213	112 <sup>1</sup> / <sub>4</sub> "	288	125	56.7
6' x 8'	183 x 244	122 <sup>1</sup> / <sub>4</sub> "	311	140	63.5
8' x 8'	244 x 244	125 <sup>3</sup> / <sub>4</sub> "	319	148	67.1
7' x 9'	213 x 274	136 <sup>1</sup> / <sub>4</sub> "	346	155	70.3
9' x 9'	274 x 274	134 <sup>3</sup> / <sub>4</sub> "	342	159	72.1
8' x 10'	244 x 305	149 <sup>3</sup> / <sub>4</sub> "	380	165	74.8
10' x 10'	305 x 305	146 <sup>3</sup> / <sub>4</sub> "	373	168	76.2
9' x 12'	274 x 366	170 <sup>3</sup> / <sub>4</sub> "	434	189	85.7
12' x 12'	366 x 366	175 <sup>1</sup> / <sub>4</sub> "	445	194	88.0

**All screens standard with 12" black drop at top.**

Extra drop may alter case dimensions. Contact Da-Lite for details.

Overall case length dimensions  $\pm 1/4"$ .

Detail dimensional drawings, wiring diagrams and installation instructions available upon request.

Specifications subject to change without notice.

Custom formats and sizes available upon request.

**All viewing surfaces will be seamless.**

**All viewing surfaces are standard with black backing except Da-Tex® and Dual Vision.**

**Audio Vision, High Contrast Audio Vision and High Contrast Cinema Perf available in sizes up to 87" x 116" in Video Format and 78" x 139" in HDTV Format.**

**WHEN ORDERING, MARK APPROPRIATE SELECTIONS:**

**Select size from charts on the other side.**

**Select viewing surface:**

- Da-Mat®
- Pearlescent
- Audio Vision
- Dual Vision
- High Contrast Audio Vision
- High Contrast Da-Mat®
- Cinema Vision
- Da-Tex® (Rear)
- High Contrast Cinema Vision
- High Contrast Cinema Perf

**Optional Accessories:**

- Single motor Low Voltage Control(LVC) - external.
- Single motor Low Voltage Control(LVC) - built-in.
- Wireless Remote Control for LVC.
  - Radio Frequency Remote
  - Radio Frequency Range Extender available
  - Infrared Remote
- Key Locking Cover Plate for 120 V Switch or LVC.
- Key Operated Switch for 120 V only (NOTE: Cannot be used with LVC).
- 220/240 Volt (50 Hz) motor.
- Video Projector Interface - external.

Project:	_____
Architect:	_____
Phone:	_____
Contractor:	_____
Phone:	_____
Supervisor:	_____
Phone:	_____
Supplier:	_____
Date:	_____
Revised:	_____

- SCB-100 RS-232 Serial Control Board - external.
  - NET-100 Ethernet-Serial Adapter
- SCB-100 RS-232 Serial Control Board - built-in. Electrical connections will be on right end of screen case on units with built-in SCB-100.
  - NET-100 Ethernet-Serial Adapter
- SCB-200 RS-232 Serial Control Board - built-in. Electrical connections will be on right end of screen case on units with built-in SCB-200.
  - NET-200 Ethernet-Serial Adapter
  - WC-200 Wall Controller
  - IR-200 Infrared Remote

**TENSIONED ADVANTAGE® DELUXE ELECTROL® SUGGESTED CEILING INSTALLATION**

