



LOAD-A-PUP

MODEL: LP500HD

⚠ WARNING

READ ALL INSTRUCTIONS BEFORE USING THE LOAD-A-PUP HD

NOTE: Failure to read instructions before use could result in injury or death.

NOTE: All initial installation adjustments to the LOAD-A-PUP should be made prior to launching boat.

Instructions for Installation and Use:

Contents:

1ea –Load-A-Pup (fully assembled), **1 ea**–Safety Strap, 2 ea J-bolts, 2 ea 5/16” Wing knobs, 2 ea Quick-clip pins.

Step 1. Select side of transom (or side of boat) to mount Load-a-Pup HD.

Step 2. Insert J-bolt through vertical square tube of frame to determine desired height of Load-a-Pup. (Usually, this would be done to position platform at or just below water level) See Figure 1.



Figure 1

Step 3. Remove and re-insert the two Quick-clip Pins from the leveling tubes to set the Load-a-Pup platform to the desired angle. (See Figure 2)



Figure 2

Step 4. Install safety strap to top of frame of the Load-a-Pup and connect to any available brace or hand-hold of boat to prevent accidental dropping of the Load-a-Pup. (See figure 3)



Figure 3

⚠ WARNING

LOAD-A-PUP IS NOT DESIGNED OR APPROVED FOR HUMAN USE

⚠ WARNING

NEVER USE THIS PRODUCT FOR ANYTHING OTHER THE INTENDED USE

⚠ WARNING

DO NOT USE THIS PRODUCT IN EXTEME WEATHER CONDITIONS i.e., LIGHTING, HIGH WINDS, ROUGH/CHOPPY WATER

⚠ WARNING

MAXIMUM WEIGHT CAPACITY IS 200 LBS.

⚠ WARNING

MAKE SURE THAT SAFETY STRAP IS ALWAYS ATTACHED TO PREVENT PRODUCT LOSS

Caution

- *Not for human use
- *For use with dogs weighing 100 lbs or less
- *Do not allow dog on platform while boat is moving
- *Do not use on boats less than 14 feet in length
- *Sides of boats must be 15 inches tall or taller
 - *Do not use on a canoe or pirogue
 - *Do not use as a diving platform
 - *Do not use as hunting stand
- *Remove unit from boat before traveling

For more information about this or other products, contact us at:

Great Day, Inc.

604 Kimbrough Dr. * Tallulah, LA 71282
* (866) 649-1918 * www.greatdayinc.com