

	Reference	Rope diameter	Sheave	Efficiency	Working load	Certification	Weight
Poulies bloqueurs							
MINI TRAXION	P07	8 - 13 mm	19 mm Self-lubricating bushings	71 %	pulley: 2.5 kN x 2 = 5 kN	CE EN 567, UIAA	165 g
					rope clamp: 2.5 kN	CE EN 12278, UIAA	
PRO TRAXION	P51	8 - 13 mm	38 mm Self-lubricating bushings	95 %	pulley: 3 kN x 2 = 6 kN	CE EN 567, UIAA	265 g
					rope clamp: 2.5 kN	CE EN 12278, UIAA	
Prusik pulleys							
MINI	P59	≤ 11 mm	25 mm Sealed ball bearings	91 %	2 kNx 2 = 4 kN	CE EN 12278, UIAA	80 g
GEMINI	P66	≤ 11 mm	25 mm Sealed ball bearings	91 %	2 x 1.5 kNx 2 = 6 kN	CE EN 12278, UIAA	130 g
Single pulleys							
RESCUE	P50	≤ 13 mm	38 mm Sealed ball bearings	95 %	4 kNx 2 = 8 kN	CE EN 12278, UIAA	186 g
FIXE	P05	≤ 13 mm	21 mm Self-lubricating bushings	71 %	2.5 kNx 2 = 5 kN	CE EN 12278, UIAA	90 g
OSCILLANTE	P02	≤ 13 mm	25 mm	50 %	2 kNx 2 = 4 kN	CE EN 12278, UIAA	55 g
ULTRALEGERE	P00	≤ 13 mm	—	—	0.5 kNx 2 = 1 kN	—	10 g
Transport pulleys							
TANDEM	P21	rope ≤ 13 mm	21 mm Self-lubricating bushings	71 %	10 kN	CE EN 12278, UIAA	195 g
TANDEM CABLE	P21 CAB	rope ≤ 13 mm	21 mm Self-lubricating bushings	71 %	10 kN	CE EN 12278, UIAA	258 g
		cable ≤ 12 mm					
TANDEM SPEED	P21 SPE	rope ≤ 13 mm	27.5 mm Sealed ball bearings	91 %	10 kN	CE EN 12278, UIAA	270 g
		cable ≤ 12 mm					