

Room Air Conditioner Specifications

PERFORMANCE										ELECTRICAL REQUIREMENTS					FEATURES					CABINET SIZE			WINDOW OPENING		WEIGHT	
Model	Energy Star	Cooling Area (see note 1)	BTU Cooling	BTU Heating	E.E.R.	Pints Per Hour	Room Air Delivery (CFM max.)	Voltage	Amps Cooling	Amps Heating	Watts Cooling	Watts Heating	Plug Cap. Amps	Receptacle	Air Exchanger	Air Direction	Fan Speeds	Auto Restart	Slide-Out Chassis	Additional Features	Width	Depth*	Height	Width (Min-Max)	Height (Min)	Net/Ship Weight (lbs)
WINDOW AIR CONDITIONERS																										
AZ3R05F2A	N	150	5000	—	9.7	0.8	118	115	4.8	—	515	—	10	A	N	2 Way	2	N	N	M	16 ¼	13 ¾	12 ⅝	16 ½ - 36	13	34.2/39.7
AZ6R05F2A	N	150	5000	—	9.7	0.8	118	115	4.8	—	515	—	10	A	N	2 Way	3	Y	N	*	16 ¼	13 ¾	12 ⅝	16 ½ - 36	13	34.2/39.7
AZ7R05F2A	Y	150	5200	—	10.7	1.1	147	115	4.5	—	485	—	10	A	N	2 Way	3	Y	N	*	16 ¼	15 ¾	12 ⅝	16 ½ - 36	13	38.6/44.1
AZ6R06F2A	N	200	6000	—	9.7	1.3	147	115	6.1	—	620	—	10	A	N	4 Way	3	Y	N	*	16 ¼	15 ¾	12 ⅝	16 ½ - 36	13	39.7/45.2
AZ7R06F2A	Y	200	6000	—	10.7	1.3	147	115	5.4	—	560	—	10	A	N	4 Way	3	Y	N	*	16 ¼	15 ¾	12 ⅝	16 ½ - 36	13	46.3/52.9
AZ6R08F2A	N	340	8000	—	9.8	1.7	224	115	7.4	—	815	—	10	A	Y	4 Way	3	Y	N	*	19 ⅞	15 ¾	12 ⅝	21 ⅝ - 36	14	46.3/52.9
AZ7R08F2A	Y	340	8000	—	10.8	1.7	224	115	7.0	—	740	—	13	A	Y	4 Way	3	Y	N	*	19 ⅞	15 ¾	12 ⅝	21 ⅝ - 36	14	59.5/66.1
AZ6R10F2A	N	450	10000	—	9.8	2.4	295	115	9.4	—	1020	—	13	A	Y	4 Way	3	Y	N	*	19 ⅞	19	14 ¾	22 ⅝ - 36	14 ¼	58.4/65
AZ7R10F2A	Y	450	10000	—	10.8	2.7	295	115	8.8	—	930	—	15	A	Y	4 Way	3	Y	N	*	19 ⅞	20 ⅝	14 ¾	19 ⅝ - 36	14 ¼	82.7/91.5
AZ7Y12F2A	Y	550	12000	—	10.8	2	280	115	9.7	—	1110	—	15	A	Y	4 Way	3	Y	Y	*	22 ⅝	21 ⅞	15 ⅜	22 ⅞ - 36	16 ¼	82.7/90.4
AZ7Y12F7A	Y	550	12000	—	10.8	2.2	280	230	4.9	—	1130	—	15	B	Y	4 Way	3	Y	Y	*	22 ⅝	21 ⅞	15 ⅜	22 ⅞ - 36	16 ¼	99.2/111.4
AZ7Y15F2A	Y	800	15000	—	10.7	3.8	460	115	12.0	—	1410	—	15	A	Y	4 Way	3	Y	Y	*	23 ⅝	25 ½	17 ⅜	23 ⅞ - 40 ½	18 ½	99.2/111.4
AZ7Y18F7A	Y	1000	18000	—	10.7	5.5	460	230	7.7	—	1730	—	15	B	Y	4 Way	3	Y	Y	*	23 ⅝	25 ½	17 ⅜	23 ⅞ - 40 ½	18 ½	105/119
AZ7R24E7A	Y	1400	24000	—	9.4	8	530	230	11.6	—	2660	—	20	C	Y	4 Way	3	Y	Y	*	26 ⅞	26 ⅞	18 ½	26 ⅝ - 42	19	122.3/136.6
HEAT/COOL WINDOW AIR CONDITIONERS																										
AZEY08F2A	Y	340	8000	3500	10.8	1.5	280	115	6.6	8.9	740	1050	13	A	Y	4 Way	3	Y	Y	*	22 ⅝	21 ⅞	15 ⅜	22 ⅞ - 36	16 ¼	73.2/80.9
AZEY12F7A	Y	550	12000	11000	10.8	2.2	280	230	4.9	15	1130	3500	20	C	Y	4 Way	3	Y	Y	*	22 ⅝	21 ⅞	15 ⅜	22 ⅞ - 36	16 ¼	85/92.5
AZEY18F7A	Y	1000	18000	16000	9.7	5.5	460	230	8.4	22	1900	4900	25	D	Y	4 Way	3	Y	Y	*	23 ⅝	25 ½	17 ⅜	23 ⅞ - 40 ½	18 ½	105/119
AZEY18F7B	Y	1000	18000	10200	9.7	5.5	460	230	8.4	15	1900	3500	20	C	Y	4 Way	3	Y	Y	*	23 ⅝	25 ½	17 ⅜	23 ⅞ - 40 ½	18 ½	105/119
AZER24E7A	Y	1400	24000	16000	9.4	8	530	230	11.6	22.5	4900	25	D	Y	4 Way	3	Y	Y	*	26 ⅞	26 ⅞	18 ½	26 ⅝ - 42	19	128/142.2	
THROUGH-THE-WALL AIR CONDITIONERS																										
AZ7T08W2A	Y	340	8000	—	9.4	1.8	283	115	8.0	—	850	—	10	A	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	59.5/70.6
AZ7T10W2A	Y	450	10000	—	9.4	2.6	283	115	9.8	—	1060	—	15	A	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	65/75
AZ7T10W7A	Y	450	10000	—	9.4	2.8	295	230	5.1	—	1060	—	15	B	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	60.6/70.6
AZ7T12W2A	Y	550	12000	—	9.4	3.3	295	115	11.1	—	1240	—	15	A	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	67.3/76.1
AZ7T12W7A	Y	550	12000	—	9.4	3.5	295	230	6.3	—	1270	—	15	B	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	68.4/78.3
AZET12W7A	Y	550	12000	10600	9.4	3.5	295	230	6.0	15	1330	3450	20	C	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	72.8/82.7
AZ6T14W7A	N	700	14000	—	9.0	4.3	318	230	7.4	—	1550	—	20	C	Y	4 Way	3	Y	Y	**	24 ⅞	20 ¼	14 ½	N/A	N/A	68.4/79.4
THROUGH-THE WALL AIR CONDITIONERS FOR A/B SLEEVES																										
AZ7A09W2A	Y	400	9200	—	9.8	2.4	280	115	8.6	—	940	—	15	A	Y	4 Way	3	Y	Y	**	26	16 ⅞	15 ⅜	N/A	N/A	84/97
AZ7A12W2A	Y	550	11800	—	9.4	3.2	280	115	11.6	—	1260	—	15	A	Y	4 Way	3	Y	Y	**	26	16 ⅞	15 ⅜	N/A	N/A	84/97
AZ7A12W7A	Y	550	11800	—	9.8	3.2	280	230	5.6	—	1200	—	13	B	Y	4 Way	3	Y	Y	**	26	16 ⅞	15 ⅜	N/A	N/A	84/97
PORTABLE AIR CONDITIONERS																										
AZ6P09S2A	N	400	9000	—	8.8	3	185	115	9.5	—	1080	—	15	A	N	1 Way	3	Y	—	***	17 ⅞	15 ½	31 ⅞	N/A	N/A	66/75
AZ6P12D2A	N	550	12000	—	10	4	235	115	10.8	—	1300	—	15	A	N	2 Way	3	Y	—	****	18 ⅞	18 ⅝	36 ⅝	N/A	N/A	79/94
AZHP12D2A	N	550	12000	11000	8.7	4	235	115	10.8	11	1300	1250	15	A	N	2 Way	3	Y	—	****	18 ⅞	18 ⅝	36 ⅝	N/A	N/A	79/94

Note 1 The square feet of cooling area listed is based on average room conditions in a moderate climate. Some exceptions are kitchens (add 4,000 BTU), high ceilings or unusual floor plans (increase 10%), warmer climates (increase 10-20%).

ADDITIONAL FEATURES

M	Mechanical control, no remote control.
*	Full function remote control, 24 hour timer on-off, Sleep mode, Energy Saver mode, LED display, C/F display change, Filter check (250 hours), Auto-restart function, Operation Mode: Cool/Fan/Dry/Auto, Easy mount window kit
**	Full function remote control, 24 hour timer on-off, Sleep mode, Energy Saver mode, LED display, C/F display change, Auto-restart function, Operation Mode: Cool/Fan
***	Simple remote control, 12 hour timer on-off, LED display, Auto-restart
****	Simple remote control, 24 hour timer on-off, LCD display, Auto-restart

Receptacle Key



Models and specifications are subject to change without notice. All models have electronic controls with remote control unless noted otherwise. 230v models are 208/230 volt and specifications listed are at 230v.