

EUROPEAN SAFETY DATA SHEET

SAFETY DATA SHEET

Page 1 of 4

HumiSeal 1B15

Revision 0
Revision date 29-Oct-2008

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name HumiSeal 1B15
Company HumiSeal Europe
Alasan House
Albany Park
Frimley Road
Camberley
Surrey
GU16 7PH
United Kingdom
Telephone +44 (0)127 6691100
Fax +44 (0)127 6691227

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Toluene	40 - 50%	108-88-3	203-625-9	F; R11 Repr Cat 3; R63 Xn; R48/20-65 Xi; R38 R67
Butanone (Butan-2-one (methyl ethyl ketone))	10 - 20%	78-93-3	201-159-0	F; R11 Xi; R36 R66 R67

3. HAZARDS IDENTIFICATION

Main hazards Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness. Highly flammable Harmful by inhalation.

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water.
Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention.
Inhalation Move the exposed person to fresh air.
Ingestion DO NOT INDUCE VOMITING. Seek medical attention.
General information Immediate medical attention is required.

HumiSeal 1B15

Revision 0
Revision date 29-Oct-2008

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO₂), dry chemical, foam.
Protective equipment Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area.
Environmental precautions Do not allow product to enter drains.
Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation of the working area.
Storage Store in original container. Store at temperatures between 5 °C and 25 °C. Keep in a cool, dry, well ventilated area. Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Toluene	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m ³ : 191 WEL 15 min limit mg/m ³ : 384
Butanone (Butan-2-one (methyl ethyl ketone))	WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 300	WEL 8-hr limit mg/m ³ : 600 WEL 15 min limit mg/m ³ : 899

Respiratory protection Wear suitable respiratory equipment when necessary. Wear: Suitable respiratory equipment.
Hand protection Chemical resistant gloves (PVC)
Eye protection Avoid contact with eyes. In case of splashing, wear: Safety glasses.
Protective equipment Avoid contact with eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid.
Colour Colourless.
Odour Aromatic.
Boiling point 82°C
Flash point 1°C

10. STABILITY AND REACTIVITY

Stability Stable.
Materials to avoid Strong oxidising agents.
Hazardous decomposition products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Corrosivity Irritating to eyes, respiratory system and skin.
Repeated or prolonged exposure Repeated or prolonged exposure may cause dermatitis.

Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 28-Jan-2009

HumiSeal 1B15

Revision 0
Revision date 29-Oct-2008

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

General information Dispose of as special waste in compliance with local and national regulations.

14. TRANSPORT INFORMATION

ADR/RID

UN 1263	Packing group II
Class 3	Hazard ID 33
Proper Shipping Name PAINT .	

IMDG

UN 1263	Packing group II
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group II
Class 3	Subsidiary risk -
Packing Instruction 307 (Cargo)	Maximum quantity 60 L
Packing Instruction 305 (Passenger)	Maximum quantity 5 L

15. REGULATORY INFORMATION

Symbols F - Highly flammable; Xn - Harmful



Risk phrases

R38 - Irritating to skin.
 R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 R63 - Possible risk of harm to the unborn child.
 R65 - Harmful: may cause lung damage if swallowed.
 R67 - Vapours may cause drowsiness and dizziness.
 R11 - Highly flammable.
 R20 - Harmful by inhalation.

Safety phrases

S16 - Keep away from sources of ignition - No smoking.

Manufactured by: Humiseal Europe,
 Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
 Phone: 44-127-669-1100 Fax: 44-127-669-1227

Print date 28-Jan-2009

HumiSeal 1B15

Revision 0
Revision date 29-Oct-2008

16. OTHER INFORMATION

Text of risk phrases in Section 2

R11 - Highly flammable.
R36 - Irritating to eyes.
R38 - Irritating to skin.
R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63 - Possible risk of harm to the unborn child.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.
R67 - Vapours may cause drowsiness and dizziness.

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. The information provided relates only to the product or material specified and does not apply if used in combination with other materials. Handle and store under inert gas. This product is not properly labelled for sale or use outside the EU.

**Manufactured by: Humiseal Europe,
Alasan House, Albany Park, Frimley Road, Camberley, Surrey, GU16 7PH, England
Phone: 44-127-669-1100 Fax: 44-127-669-1227**

Print date 28-Jan-2009