

Material Safety Data Sheet

Section 1. C	Section 1. Chemical Product and Company Identification		
Common Name	BRAYCO 300	Code	0000001464 (27006-AW)
Supplier	Air BP Lubricants Maple Plaza II - 1N	Validation Date	10/20/2003
	Six Campus Drive Parsippany, NJ 07054 U.S.A. General information: (973) 401-4350	Print Date	10/20/2003
Synonym	Not available.		
Trade name	Not available.	Responsible Name	Froduct Stewardship
Material Uses	Industrial applications	In Case of CHE	MTREC (800) 424-9300
Manufacturer	ASTROL INDUSTRIAL NORTH AMERICA INC. 1001 WEST 31ST STREET DOWNERS GROVE, IL 60515-1280 Product Information: 630 241-4000	<u>Emergency</u>	

Name	CAS #	% by Weight	Exposure Limits
STILLATES PETROLEUM, HYDROTREATED LIGHT NAPHTHENIC	64742-53-6	65-70	ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral ACGIH (United States). STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral
LUBRICATION OILS, PETROLEUM, C15-30, HYDROTREATED NEUTRAL OIL-BASED.	72623-86-0	20-25	ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral ACGIH (United States). STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	1-5	ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist ACGIH (United States). STEL: 10 mg/m ³ 15 minute(s). Form: Mist
BENZENESULFONIC ACID, DI-C10-C18 DERIVATIVES	93820-57-6	1-5	Not available.

BRAYCO 300	Page: 2/8
Section 3. Hazards	dentification
Physical state / Appearance Mild. Petroleum Odor Ølear. Brownish-red. Liqui	Iquid.
Emergency Overview	WARNING! CAUSES EYE AND SKIN IRRITATION. MIST: MAY CAUSE RESPIRATORY TRACT IRRITATION. Avoid contact with skin and eyes. Wash thoroughly after handling. Do not ingest. However, in light of good industrial bugings, exposure to any chemical should be kent to a minimum
Routes of Entry	light of good industrial hygiene, exposure to any chemical should be kept to a minimum. Skin Contact. Eye contact. Inhalation. Ingestion.
Potential Acute Health Eff Eyes	ects Causes eye irritation.
Skin	Causes skin irritation.
Inhalation	Vapor: Solution may cause irritation of mouth, throat, and esophagus. High vapor concentrations can cause headaches, dizziness, drowsiness, and nausea, and may lead to unconsciousness. Vapor: Prolonged repeated exposure may cause chemical pneumontitis.
Ingestion	Oral LD50: Not established. Ingestion may cause gastrointestinal irritation and diarrhea.
No additional remark.	
Potential Chronic Health Effects	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. CARCINOGENIC EFFECTS: No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA). MUTAGENIC EFFECTS: No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen. TERATOGENIC EFFECTS: No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.
Medical Conditions Aggravated by Overexposure:	Repeated or prolonged exposure is not known to aggravate medical condition.
Over-exposure signs/symptoms See Toxicological Informat	Not available.

Section 4. First Aid Measures

Eye Contact	Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention.
Skin Contact	Wash contaminated skin with soap and water. Get medical attention if irritation develops. Wash clothing before reuse.
Inhalation	Breathing difficulty or Respiratory tract irritation: Remove to fresh air. If the victim is not breathing, perform mouth-to-mouth resuscitation. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	If affected person is conscious, give plenty of water to drink. NEVER give an unconscious person anything to ingest. Do not induce vomiting. ASPIRATION HAZARD. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention immediately.
Notes to Physician	Not available.

Continued on Next Page

BRAYCO 300	Page: 3/8
Section 5. Fire Fig	hting Measures
Flammability of the Product	May be combustible at high temperature.
Auto-ignition temperature	Not available.
Flash Point	Open cup: 135°C (275°F) (Cleveland.).
Flammable Limits	Not available.
Products of Combustion	These products are carbon oxides (CO, CO ₂).
Fire Hazards in Presence of Various Substances	Non-flammable in presence of open flames, sparks and static discharge, of shocks, of heat.
Explosion Hazards in Presence of Various Substances	This material is not explosive as defined by established regulatory criteria.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam.
	Cool closed containers exposed to fire with water. Hot containers may explode. Use water spray to keep fire exposed containers cool. Do not use water jet.
Protective Clothing (Fire)	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and ful turnout gear.
Special Remarks on Fire Hazards	None identified.
Special Remarks on Explosion Hazards	None identified.

Section 6. Accidental Release Measures

Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal. Do not allow any potentially contaminated water including rain water, runoff from fire fighting or spills to enter any waterway, sewer or drain.
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal. Do not allow any potentially contaminated water including rain water, runoff from fire fighting or spills to enter any waterway, sewer or drain.

Section 7. Handling and Storage

Rerosol.: Over-exposure by inhalation may cause respiratory irritation. Do not ingest. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. However, in light of good industrial hygiene, exposure to any chemical should be kept to a minimum.

Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Section 8. Exposu	re Controls and F	Personal Protection
Engineering Controls	ventilation or other e their respective occu safety work practices	sure by inhalation may cause respiratory irritation. Provide exhaust engineering controls to keep the airborne concentrations of vapors below upational exposure limits. In accordance with good industrial hygiene and s, airborne exposures should be controlled to the lowest extent r, in light of good industrial hygiene, exposure to any chemical should be
Personal Protection Eyes	Safety glasses with s Chemical splash gog	
Body	Avoid prolonged or rewith skin. Wear cloth footwear that cannot by chemicals or oil.	ing and
Respiratory	A respirator is not ne normal and intended product use. Wear respirator when vent inadequate.	conditions of appropriate
Hands	Impervious gloves.	
Feet	Not applicable.	
Protective Clothing (Pictograms) Personal Protection in Case of a Large Spill		suit. Boots. Gloves. Suggested protective clothing might not be sufficient; BEFORE handling this product.
Product Name	•	Exposure Limits
DISTILLATES PETROLEI HYDROTREATED LIGHT		ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Oil mist, mineral
LUBRICATION OILS, PE HYDROTREATED NEUT		 ACGIH (United States). STEL: 10 mg/m³ 15 minute(s). Form: Oil mist, mineral ACGIH (United States). TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral OSHA (United States). TWA: 5 mg/m³ 8 hour(s). Form: Oil mist, mineral ACGIH (United States).
DISTILLATES, PETROLE HYDROTREATED HEAV		STEL: 10 mg/m ³ 15 minute(s). Form: Oil mist, mineral ACGIH (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist OSHA (United States). TWA: 5 mg/m ³ 8 hour(s). Form: Mist ACGIH (United States).
BENZENESULFONIC AC DERIVATIVES	ID, DI-C10-C18	STEL: 10 mg/m ³ 15 minute(s). Form: Mist Not available.
Consult local authorities fo	or acceptable exposure	limits.

BRAYCO 300			Page: 5/8
Section 9. Physical and Chemical Properties			
Physical state / Appearance	Equid.	Odor	Mild. Petroleum Odor
Boiling/Condensation Point	Not available.	Taste	Not available.
Melting/Freezing Point	Not available.	Color	Clear. Brownish-red. Liquid.
pH (Concentration)	Not applicable.		
pH Dilution % and Value	Not applicable.		
Critical Temperature	Not available.		
Specific Gravity	0.886 (Water = 1)		
Vapor Pressure	Not available.		
Vapor Density	Not available.		
Volatility	Not available.		
Odor Threshold	Not available.		
Evaporation Rate	Not available.		
VOC	455.39 (g/l).	VOC Method	DETERMINED.
Viscosity	Not available.		
Solubility	Insoluble in cold water, hot water.		
Physical Chemical Comments	Not available.		

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	Avoid excessive heat.
Incompatibility with Various Substances	Strong oxidizing materials
Hazardous Decomposition Products	a parbon oxides (CO, CO2), sulfur oxides (SO2, SO3), nitrogen oxides (NO, NO2)
	Will pat acourt

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Toxicity to Animals	LD50: Not available. LC50: Not available.	
Chronic Effects on Humans	 Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis. CARCINOGENIC EFFECTS: No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA). MUTAGENIC EFFECTS: No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen. TERATOGENIC EFFECTS: No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic. 	
Continued on I	Continued on Next Page	

BRAYCO 300	Page: 6/8
	REPRODUCTIVE EFFECTS: No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.
Other Toxic Effects on Humans	No specific information is available in our database regarding the other toxic effects of this material for humans.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.
Special Remarks on Othe Toxic Effects on Humans	

Section 12. Ecological Information Ecotoxicity Not determined. **BOD** and COD Not determined. **Biodegradable/OECD** Not determined. Mobility Not determined. zarbon oxides (CO, CO₂), sulfur oxides (SO₂, SO₃...), nitrogen oxides (NO, NO₂...) Products of Degradation Toxicity of the Products of Not determined. Biodegradation **Special Remarks on the** No additional remark. Products of Biodegradation

Section 13. Disposal Considerations

Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. Keep out of waterways. Disposal of this material to the land may be banned by federal law (40 CFR 268).

USED OIL

RCRA Waste Code(s)

Waste Stream Not determined.

Consult your local or regional authorities.

Section 14. Transport Information

DOT Classification	Not a DOT controlled material (United States).	
Marine Pollutant	Not pollutant.	
Special Provisions for Transport	NOT REGULATED	
ADR/RID Classification	Not determined.	
Continued on Next Page		

Г

IMO/IMDG Classification Not determined.

ICAO/IATA Classification Not determined.

Section 15. Regulatory Information

U.S. Federal Regulations	
	SARA 302/304 emergency planning and notification: No products were found.
	SARA 311/312 MSDS distribution - chemical inventory - hazard identification: BRAYCO 300: immediate health hazard.
	SARA 313 toxic chemical notification and release reporting: No products were found.
	Clean Water Act (CWA) 307: No products were found. Clean Water Act (CWA) 311: No products were found. Clean air act (CAA) 112 accidental release prevention: No products were found. Clean air act (CAA) 112 regulated toxic substances: No products were found.
	Clean air act (CAA) 112 regulated flammable substances: No products were found.
State Regulations	Massachusetts RTK: Highly refined mineral oil
	California prop. 65: No products were found.
Inventory Lists	SCA 8(b) inventory: In compliance.
	CEPA DSL: Not listed.
	Australia (NICNAS): Not listed.
	Korea (TCCL)Not Listed.
	Philippines (RA6969): In compliance.
	MITI: In compliance.
	EINECS: In compliance.

Section 16. O	ther Information	
Label Requirements	CAUSES EYE AND SKIN IRRITATION. MIST: MAY CAUSE RESPIRATORY TRACT IRRITATION.	
Hazardous Mate Information Sys (U.S.A.)	1 Fire Hazard	
References	Not available.	
Other Special Considerations	PETROLEUM OIL: STEL = 10 mg/M3. Using terminology of the International Agency for Research on Cancer (IARC), the petroleum distillates listed in Section II are classified by the supplier as severely processed. Not all those listed in Section II may be present. The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200.	
Continued on Next Page		

BRAYCO 300

Validated by Product Stewardship on 10/20/2003.

Printed . (PrintDate(10/20/2003.

Page: 8/8

CHEMTREC (800) 424-9300

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.