

KPT-SPD201FHEV



Introduction

KPT-SPD201FHEV is an Outdoor SPEED DOME PTZ CAMERA.

This unit can monitor the target area efficiently with the PTZ control in all weather conditions.

Special Features

- ⊙ Programmable AE per Preset
- ⊙ 360° Endless Pan (Pan Speed 120°/Sec)
- ⊙ Vandal Proof
- ⊙ Wall/Ceiling/Flush Mount

Model		KPT-SPD201FHEV
Signal Format		NTSC
Camera	Device	1/4" Sony Super HAD CCD
	Total Pixels	410K Pixels [811(H) x 508(V)]
	Resolution	480 TV Lines
	MIN. Illuminance	1 Lux (Day) 0.001 Lux (Night with DSS)
	Focus	Auto / Manual
	Iris	Auto
	BLC	On / Off
	Flickerless	FL On / Off
	Zoom	22 X Optical Zoom and 10 X Digital Zoom
	White Balance	Auto / Manual / Indoor / Outdoor
	Focal Length	f=3.9 ~ 85.8mm
	Day & Night	Day / Night / Auto
	Pan/Tilt	Range
Pan/Tilt Speed		Manual : 0.05° ~ 150/sec (Zoom Proportional)
		Preset : 360° /sec Swing : ~ 60° /sec (Zoom Proportional)
Preset		127 Presets
Privacy Zone		8 Zones
Pattern		4 Patterns (MAX. 1 Minute Each)
Swing	8 Swings	
Group	8 Groups (MAX. 20 Entries)	
General	Sensor In/Out	8 Input / 4 Output
	Other	Auto Flip / Auto Parking
	Communication	RS-485
	Power	AC 24V / 1.5 A (Without Fan & Heater) AC 24V / 2A (With Fan & Heater)
	Dimension	252(φ) x 319(H)mm
Operating Temp.	0° C ~ 40° C / 32° F ~ 104° F	

KT&C USA

KT&C USA, Inc.

3240 Wilshire Blvd., Suite 501 Los Angeles, CA 90010

T: 213-381-0061 F: 213-381-0064

Email : sales@ktnusa.com www.ktnusa.com

