

## Outdoor Starter Kit Contents



Luk Outdoor Camera  
Luk USB Receiver Module  
USB Cable  
Wall/Overhang/Post Mount Bracket  
Window Decals  
Install CD  
QuickStart Setup Guide

## Outdoor Camera Specifications

The DLC-810e LukWerks Outdoor Camera is weatherproof and designed for use in most outdoor environments.

### Camera Features

Processing Power	400 MHz DSP
Onboard Image Encoding	Windows® Media Video 9
Onboard Image Processing	Motion detection up to 16 zones, Auto brightness,
Resolution	Selectable: 640 X 480 or 320 X 240 pixels
Frame Rate	Selectable: 15, 10 or 5 frames/second
Bit Rate	Selectable
Illumination	2 lx minimum per IEC 61146-1
Color Depth	10 bits

### Lens

Focus	Preset
Viewing Angle	80° (diagonal)
Firmware Updates	Selectable: Manual or Automatic

## **Operating Environment**

### Temperature Range

Operating +0°F to +110°F (-18°C to +44°C)

Storage -4°F to +140°F (-20°C to +60°C)

Humidity (storage and operating) 5% to 95% (relative; non-condensing)

Voltage 110/120 Volts AC, 50/60 Hz

Property Size Up to 8,000 square feet

## **Physical Metrics**

Power Consumption 15 Watts

Camera Body Dimensions Height: 2.0 inch (50 mm); Width 4.72 inch (120 mm);  
Depth: 8 inch (200 mm)

Camera Weight 1.1 lb (500 g)