

CODES	DOVB 33042/SS	DOVB 33041 / WH	DOVB 33040 / BL	DFP 330420 / SS	DFP 330410 / WH	DFP 330400 / BL
General	Electronically Controlled	Electronically Controlled	Electronically Controlled	Electronically Controlled	Electronically Controlled	Electronically Controlled
DESTINATION	N.A.	N.A.	N.A.	CANADA (French)	CANADA (French)	CANADA (French)
Feature upper/single	convection	convection	convection	convection	convection	convection
Feature lower	thermal	thermal	thermal	thermal	thermal	thermal
Size	30"	30"	30"	30"	30"	30"
Fuel	Electric	Electric	Electric	Electric	Electric	Electric
Color	Stainless Steel	White	Black	Stainless Steel	White	Black
Appearance Description						
Control Panel						
Color	Stainless Steel	White	Black	Stainless Steel	White	Black
Display frame	Black	Dark Grey	Dark Grey	Black	Dark Grey	Dark Grey
Control Panel Corners	SS Sharp 90 degree all 4	Rounded all 4 (min radius)	Rounded all 4 (min radius)	SS Sharp 90 degree all 4	Rounded all 4 (min radius)	Rounded all 4 (min radius)
Control Panel	Stainless Steel bended	Optical White	Black	Stainless Steel bended	Optical White	Black
User interface	Knobs / Buttons	Knobs / Buttons	Knobs / Buttons	Knobs / Buttons	Knobs / Buttons	Knobs / Buttons
Button	FCI - SS Plastic	FCI - White Plastic	FCI - Black Plastic	FCI - SS Plastic	FCI - White Plastic	FCI - Black Plastic
Button color	SS	White	Black	SS	White	Black
Knob	Plastic VG conic base	Plastic VG conic base	Plastic VG conic base	Plastic VG conic base	Plastic VG conic base	Plastic VG conic base
Knob color	Stainless Steel	White	Black	Stainless Steel	White	Black
Knob Index for 0 position	Black dot	Light Grey dot	Light Grey dot	Black dot	Light Grey dot	Light Grey dot
Silicon ring around knob	Black	Dark Grey	Dark Grey	Black	Dark Grey	Dark Grey
Graphics	Light Grey	White	Light Grey	Light Grey	White	Light Grey
Oven Door(s)						
Color	Stainless Steel	White	Black	Stainless Steel	White	Black
Door	Stainless Steel bended	Optical White	Black	Stainless Steel bended	Optical White	Black
Inner Counter Door Color	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling
Frame of door window	Black	Dark Grey	Dark Grey	Black	Dark Grey	Dark Grey
Window	Black dotted uniform area	Dark Grey dotted uniform area	Dark Grey dotted uniform area	Black dotted uniform area	Dark Grey dotted uniform area	Dark Grey dotted uniform area
Handle style	Rectangular Alum bar SS	Rectangular Alum bar White	Rectangular Alum bar Black	Rectangular Alum bar SS	Rectangular Alum bar White	Rectangular Alum bar Black
Handle color	Stainless Steel	White	Black	Stainless Steel	White	Black
Horizontal trim color	Stainless Steel	Silver	Black	Stainless Steel	Silver	Black
Door Corners	Sharp 90 degree all 4	Rounded all 4 (min radius)	Rounded all 4 (min radius)	Sharp 90 degree all 4	Rounded all 4 (min radius)	Rounded all 4 (min radius)
Feature Content Description						
Control / oven Features						
Control type	Electronic Programmer Hawk	Electronic Programmer Hawk	Electronic Programmer Hawk	Electronic Programmer Hawk	Electronic Programmer Hawk	Electronic Programmer Hawk
Bake wattage	3500 W	3500 W	3500 W	3500 W	3500 W	3500 W
Grill wattage	3500 W	3500 W	3500 W	3500 W	3500 W	3500 W
Convection wattage	Conv. Bake: 2500 W -- others 3500 W	Conv. Bake: 2500 W -- others 3500 W	Conv. Bake: 2500 W -- others 3500 W	Conv. Bake: 2500 W -- others 3500 W	Conv. Bake: 2500 W -- others 3500 W	Conv. Bake: 2500 W -- others 3500 W
True European Convection	top oven	top oven	top oven	top oven	top oven	top oven
Self clean	both ovens	both ovens	both ovens	both ovens	both ovens	both ovens
Upper Heating Element	3500 W	3500 W	3500 W	3500 W	3500 W	3500 W
Lower heating Elements	3000 W	3000 W	3000 W	3000 W	3000 W	3000 W
Circular Element	2500 W (upper oven)	2500 W (upper oven)	2500 W (upper oven)	2500 W (upper oven)	2500 W (upper oven)	2500 W (upper oven)
Grill	3500 W	3500 W	3500 W	3500 W	3500 W	3500 W
Oven - upper of double or single						
Net Capacity (dm3 //cbft)	78,9 // 2,78	78,9 // 2,78	78,9 // 2,78	78,9 // 2,78	78,9 // 2,78	78,9 // 2,78
Cavity Color	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling
Chromed racks	no	no	no	no	no	no
Porcelain enameled racks	2 Black enameled racks	2 Black enameled racks	2 Black enameled racks	2 Black enameled racks	2 Black enameled racks	2 Black enameled racks
Telescopic chromed rack	1 Telescopic chromed rack	1 Telescopic chromed rack	1 Telescopic chromed rack	1 Telescopic chromed rack	1 Telescopic chromed rack	1 Telescopic chromed rack
Racks Position	4	4	4	4	4	4
Oven lights	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen
Grill set (basin + anti splash)	1 Black Color Enameled	1 Black Color Enameled	1 Black Color Enameled	1 Black Color Enameled	1 Black Color Enameled	1 Black Color Enameled
Meat probe	no	no	no	no	no	no
Oven - lower of double						
Net Capacity (dm3 //cbft)	83,8 // 2,96	83,8 // 2,96	83,8 // 2,96	83,8 // 2,96	83,8 // 2,96	83,8 // 2,96
Cavity Color	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling	Black Enameling
Chromed racks	no	no	no	no	no	no
Porcelain enameled racks	2 Black enameling racks	2 Black enameling racks	2 Black enameling racks	2 Black enameling racks	2 Black enameling racks	2 Black enameling racks
Telescopic chromed rack	no	no	no	no	no	no
Racks Position	4	4	4	4	4	4
Oven lights	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen	2x20W Halogen
Grill set (basin + anti splash)	no	no	no	no	no	no
Dimensions - catalog (mm /Inch)						
Overall dim - width	746 / 29 23/64"	746 / 29 23/64"	746 / 29 23/64"	746 / 29 23/64"	746 / 29 23/64"	746 / 29 23/64"
Overall dim - height	1220 / 48 1/32"	1220 / 48 1/32"	1220 / 48 1/32"	1220 / 48 1/32"	1220 / 48 1/32"	1220 / 48 1/32"
Overall dim - depth	619 / 24 3/8"	619 / 24 3/8"	619 / 24 3/8"	619 / 24 3/8"	619 / 24 3/8"	619 / 24 3/8"
Cutout - width	710 // 28"	710 // 28"	710 // 28"	710 // 28"	710 // 28"	710 // 28"
Cutout - height (min)	1215 // 47-13/16"	1215 // 47-13/16"	1215 // 47-13/16"	1215 // 47-13/16"	1215 // 47-13/16"	1215 // 47-13/16"
Cutout - depth (min)	610 // 24"	610 // 24"	610 // 24"	610 // 24"	610 // 24"	610 // 24"
Approx ship weight (kg)	127 / 280	127 / 280	127 / 280	127 / 280	127 / 280	127 / 280
Power / Ratings (240 V, 50 Hz) Monofase						
KW rating at 240 V	7.000	7.000	7.000	7.000	7.000	7.000
Amps at 240 V	~ 30.9	~ 30.9	~ 30.9	~ 30.9	~ 30.9	~ 30.9
Cable	X	X	X	X	X	X