


**200 Series Built-in Combination
Steam and Convection Oven**
Width 24" (60 cm)



Right-hinged

ED 220-610*

Stainless steel

ED 220-630*

Aluminum

Left-hinged

ED 221-610*

Stainless steel

ED 221-630*

Aluminum

* Limited availability after July 2007.

Included Accessories:

ED 220/221-610/630*

– Series 200 design in stainless steel or aluminum. Perfect unity when combined with EB 200.

– Baking up to 450°F. Can be combined with variable humidity from 0 to 100%. Juicy roast or bread with a crispy crust.

– Cooking in steam at defined temperatures and humidity levels with temperature probe.

The gentlest and tastiest way of preparing every dish without overbroiling, burning, or falling apart.

Fresh steam system with water supply and drainage.

Pressureless steaming.

Oven interior volume 1.48 cu.ft.

Convection only and Convection with four humidity settings 100%, 80%, 60%, and 30%.

Condensation.

Misting.

60 W halogen lighting.

Electronic precision temperature control from 85° F – 450° F.

Large function display.

Automatic cooking time.

Actual temperature display: "Thermo Test".

Integrated core temperature sensor with meat probe with digital read out. Programmable from 85° F to 210° F and automatic shut-off.

Heat-insulated door with two-fold glazing.

Hygienic stainless steel interior with cleaning aid.

Steam suppression/steam removal.

Automatic drying of oven interior.

Cooled housing with temperature protection.

Grease filter protecting the convection fan.

Side opening door through 180° with tinted glass front.

Child and vacation lock.

Automatic boiling point detection.

One oven tray, one perforated pan, one rack, inlet hose, drain hose attached.

Pressure regulator, shipped with connection sets, which accommodates water pressure from 29 psi to 87 psi. If incoming water pressure exceeds 87 psi, you must order DR 220-010 (see below) to reduce water pressure.

Installation accessories:

DR 220-010 Pressure regulator

3/4" connection for water pressure from 87 psi to 145 psi.

GZ 010-011 Extension for

water inlet and outlet.

Optional accessories:

KB 220-000 Additional

stainless steel oven tray, 1/2" deep.

KB 220-324 Additional

stainless steel perforated pan.

GR 220-046 Additional wire rack.

KB 220-114 stainless steel unperforated

cooling insert 1 1/2" deep, 1/2 tray size.

KB 220-124 stainless steel

perforated cooking insert 1 1/2" deep, 1/2 tray size.

Planning notes:

4' Power cable (hardwire required).

Hinging must be specified when ordering as the door is not interchangeable.

Plan minimum distance of 2" between two ovens installed side by side when handles in the middle or 3/4" when centered around hinged sides.

Cold water inlet 3/4".

Supplied drain hose ø=1".

Connect supplied drain hose to a 2" ø house drain pipe.

The water connection must lay at least 4 inches below the appliance.

If the hardness of the water exceeds 7° dH, a water softening system must be installed when connecting the appliance (ion exchanger or water filter). Please contact your plumber for details.

Rating:


Total rating: 2.9 kW

Total Amps: 15

220-240V / 60 Hz



ED 220 as seen from behind:



ED 220 as seen from the side:

