

# French Door Refrigerators

EI23BC36I S, EI23BC36I W, EI23BC36I B



### Cool Zone™ Drawer

This drawer keeps contents chilled, so it's perfect for wine and beer or even snacks and juice boxes.



### Luxury-Glide™ Freezer Drawer

Two Luxury-Glide™, full-width baskets are fully-extendable and have adjustable dividers. There's room to store everything, making it easy to always have frozen pizza and snacks on hand for an impromptu gathering.



### Luxury-Design™ Glass Shelves

Removable, all-glass shelves crafted for exceptional beauty and function.



### PureAdvantage® Filtration Systems

Our filtration system keeps clean, filtered air circulated throughout to prevent odor transfer and keeps fresh, clean ice at your fingertips.

Replacement Water Filter – PN# EWF01  
Replacement Air Filter – PN# EAFCBF

## 23 CU. FT. COUNTER-DEPTH FRENCH DOOR REFRIGERATORS

### Capacities

Total Capacity	22.6 Cu. Ft.
Fresh Food Volume	15.7 Cu. Ft.
Freezer Volume	6.9 Cu. Ft.
Total Shelf Area	26.9 Sq. Ft.
Fresh Food Shelf Area	19.2 Sq. Ft.
Freezer Shelf Area	7.7 Sq. Ft.

### Exterior

Signature Soft-Arc Doors and Handle Design	Yes
IQ-Touch™ Electronic Controls	Yes
Door Hinge Covers	Yes

### Fresh Food Conveniences

PureAdvantage® Water & Ice / Air Filtration	Yes
Water Filter Location	Bottom Left
Temp Alarm System / Door Ajar Alarm / Power Failure Alarm	Yes
Luxury-Design™ Glass Shelves	4 Half Width
Luxury-Glide™ Humidity-Controlled Left Crisper	Yes
Luxury-Glide™ Humidity-Controlled Right Crisper	Yes
Cool Zone™ Drawer	Yes
Perfect Temp Drawer™	
Wine Rack	
Clear Gallon Adjustable Door Bins	2
Clear 2-Liter/1/2-Gallon Removable Door Bins	3
Locking Clear Utility Bin	Yes
Tilt-Out Can Racks	2
Luxury-Design™ Ramp-Up Multilevel Lighting – Incandescent	Yes

### Freezer Conveniences

Automatic Ice Maker	Yes
Ice Maker On/Off	Yes
Fast Freeze™	Yes
Lock	Yes
Self-Closing Drawer	Yes
Sliding Full-Width Freezer Baskets	2 Luxury-Glide™ (with Dividers)
Plastic Basket Tray	1
Tilt-Out Wire Door Racks	
Luxury-Design™ Ramp-Up Multilevel Lighting – Incandescent	Yes

### Additional Features


ENERGY STAR®	Yes
Sabbath Mode (Star-K® Certified)	Yes

### Specifications

Color –	
Stainless Steel	S
White	W
Black	B
Overall Exterior Dimensions –	
Height (with Hinges and 3/8" Rollers)	69-1/2"
Width	35-5/8"
Depth (to Center of Arc)	28-3/16"
(with 90° Door Open)	42-9/16"
(with Drawer Fully Extended Including Handle)	45-7/8"
Power Supply Connection Location	Right Bottom Rear
Water Inlet Location	Left Bottom Rear
Voltage Rating	120V/60Hz/15 or 20A
Connected Load (kW Rating) @ 120 Volts†	1.02
Minimum Circuit Required (Amps)	15
Shipping Weight (Approx.)	345 Lbs.

†An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (NFPA 70) and local codes & ordinances.

NOTE: Always consult local and national electric & plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [electroluxappliances.com](http://electroluxappliances.com). Specifications subject to change.



## Counter-Depth French Door Refrigerator Specifications

- Product Weight – 335 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (NFPA 70) and local codes & ordinances.
- Voltage Rating – 120V/60Hz/ 15 or 20 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.02kW
- Amps @ 120 Volts = 8.5 Amps
- Always consult local and national electric & plumbing codes.
- Floor should be level surface of hard material, capable of supporting fully loaded refrigerator.
- When installing refrigerator adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 120° to 180° door swing, providing complete drawer/crisper access and removal. (*Absolute 4-1/2" minimum clearance will ONLY allow for 90° door swing which will provide drawer/crisper access with restricted removal.*)
- To ensure optimum performance, avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.

- For proper ventilation, front grille MUST remain unobstructed.
- Recess electrical outlet when possible.
- Water recess on rear wall recommended to prevent water line damage.
- Water Pressure – Cold water line must provide between 30 and 100 pounds per square inch (psi).
- Copper tubing with 1/4" O.D. recommended for water supply line with length equal to distance from rear of unit to household water supply line plus 7 additional feet. Optional Water Supply Installation Kits available.
- Adjustable front rollers to assist with door alignment.

## "Built-In Look" Specifications

- Minimum opening of 70-1/4" H x 36" W x 25" D required to allow for ease of installation, proper air circulation, and plumbing/electrical connections.
- Remove all wall/floor molding prior to installation.

**Note:** For planning purposes only. Refer to Product Installation Guide on the web at [electroluxappliances.com](http://electroluxappliances.com) for detailed instructions.