

Warmer Drawer

EW30WD55G S



1.6 Cu. Ft. Stainless Steel Interior

Large capacity warmer drawer has 1.6 cubic feet of usable space to keep an entire meal warm until serving time. Stainless steel interior cleans up fast and easily.



Bread Proofing

For best results, the Bread Proofing setting provides the perfect combination of moisture and warmth to raise dough evenly without cooking.



Moist or Dry Vent Control

Adjustable humidity controls deliver optimal serving results by providing the precise amount of humidity to ensure certain dishes stay moist while others remain dry.



Half-Width Rack

Drawer features a convenient half-width rack for small dishes and breads, also providing loading flexibility to accommodate a variety of prepared foods.

30" WARMER DRAWER

| | |
|----------|-------------|
| Capacity | 1.6 Cu. Ft. |
|----------|-------------|

Features

| | |
|--|-----|
| Perfect Set™ Electronic Controls | Yes |
| Blue LED Display | Yes |
| Automatic Shutoff – 4 hour | Yes |
| Humidity Control | Yes |
| Heating Element (Watts) | 450 |
| Luxury-Glide™ Full-Extension Drawer Glides | Yes |
| Element "ON" Blue Indicator Light | Yes |
| Stainless Steel Drawer Interior | Yes |
| Half-Width Rack | Yes |

Additional Features

| | |
|---|-----|
| Signature Soft-Arc Drawer Front and Handle Design | Yes |
|---|-----|

Specifications

| | |
|---|-------------------|
| Drawer Interior Dimensions – | |
| Height | 6-1/2" |
| Width | 20-15/16" |
| Depth | 19-1/4" |
| Overall Exterior Dimensions – | |
| Height | 11-1/4" |
| Width | 30" |
| Depth (to Front Drawer Corner) (Fully Extended Including Handle) | 23-3/8" 45" |
| Temperature Range | 80°F – 210°F |
| Power Supply Connection Location | Right Center Rear |
| Voltage Rating | 120V/60Hz/15A |
| Connected Load (kW Rating) @ 120 Volts [†] | 0.45 |
| Amps @ 120 Volts | 3.75 |
| Minimum Circuit Required (Amps) | 15 |
| 60" Electrical Cable | Included |
| Approved for Under-Counter Installation | Yes |
| Product Weight | 65 Lbs. |
| Shipping Weight | 80 Lbs. |

[†]For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

NOTE: Always consult local and/or national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at www.electroluxappliances.com. Specifications subject to change.

