

Performance



Performance 2

- Vented ATT™ tweeter that floats freely in a discrete enclosure. Along its length are strategically positioned vents eliminating the colouration which plagues traditional closed-back designs. This unique venting system means Performance's high frequency drivers literally 'breathe', resulting in an open yet detailed sound.
- Continuous Profile Cone (CPC™) technology driver. The aluminium cone surface and critically placed ridges ensure excellent rigidity and therefore minimum distortion.
- Dual Value Parallel (DVP) capacitor values for maximum crossover performance. The resultant crossover helps Performance 2 achieve incredible accuracy
- ClarityCap® capacitors - renowned for their astounding signal resolution - and are used in all critical parts of the crossover.
- Cabinet now made from an even more effective formulation of the original proprietary polymer resin material, delivering incredible inherent mechanical strength
- Subtle modifications to the internal structure achieve a more effective use of cabinet volume for a carefully enhanced bass response
- For sonic perfection, Mordaunt-Short has created a bespoke stand for Performance 2 which provides an inert, acoustically neutral foundation aiding detail and rhythm

Performance 2 specifications

Recommended amplifier power	15 – 150 Watts
Sensitivity	89dB/2.83V/1m
Drive units	Tweeter: 1 x 25mm (1") ATT™ aluminium dome tweeter Woofer: 1 x 165mm (6.5") aluminium 3 rd generation CPC™ woofer
Impedance (ohms)	4-8 ohms
Frequency response	48Hz – 30kHz
Crossover	Damped 2 nd order with DVP
Ported	1 front
Dimensions (w x h x d)	239 x 486 x 361mm (10 x 19 x 12")
Weight	12kg (26.4lbs)
Finishes	Granite Grey Midnight Black Silver



MORDAUNT-SHORT

Mordaunt-Short, Gallery Court, Pilgrimage Street, London SE1 4LL, England

www.mordaunt-short.com

Performance



MORDAUNT-SHORT

Mordaunt-Short, Gallery Court, Pilgrimage Street, London SE1 4LL, England

www.mordaunt-short.com

Issued: June 09