

# C60

## Xantrex C series - charge controller C60 - 12...24V DC - load 60A



### Main

Range of product	Xantrex C series
Device short name	C60
Product or component type	Charge controller
Battery voltage	12 V DC 24 V DC
Battery type	Lead-acid battery adjustable Ni-Cd adjustable

### Complementary

Input voltage	$\leq 55$ V DC - open circuit
Voltage drop	0.3 V through controller
Load current	60 A at 25 °C
Peak current	85 A
Typical current consumption	15 mA operating 3 mA idle
Protection type	External circuit breaker 60 A
Enclosure type	Ventilated
Enclosure material	Powder coated steel
Device mounting	Wall mounted vertical
Cable entry	3/4" and 1" knock-outs
Height	254 mm
Width	127 mm
Depth	63.5 mm
Product weight	1.4 kg

### Environment

AWG gauge	AWG 10
Ambient air temperature for operation	0...40 °C
Operating altitude	4572 m
Standards	UL 1741 CSA 22.2 No 107.1-95
Marking	CE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.