

# PVX-3050T Solar Battery

## Manufactured by Concorde Battery Corporation

### Description of Solar Battery:

VRLA-AGM Deep Cycle Battery for Off Grid and Grid Tied Systems.

Sun Xtender batteries provide safe, reliable and long lasting power.

Environmentally friendly, there is no exposed lead on Sun Xtender batteries.  
100 percent recyclable.

Sustainable, Clean, Renewable Energy Storage.

Since 1987, Sun Xtender solar batteries have been hand crafted for quality in the U.S.A. Valve regulated lead acid batteries with AGM construction (VRLA-AGM) is the original AGM design adopted by the military. Non-spillable construction prohibits any electrolyte leaking or spewing, allowing the battery to be used upright or on its end or side. The maintenance free AGM design means no water replenishment - ever.

Utilizing pure lead calcium grids, the Sun Xtender battery plates are thicker than the industry standard for longer cycle life, increased reliability and power. The low impedance AGM design allows for excellent charge acceptance and there is no current limit required with controlled voltage charging.

The Sun Xtender Battery product line features proprietary PolyGuard™ Microporous Polyethylene Separators, shielding the positive plates against shorting, shock or vibration. No other manufacturers offer this dual layer insulation protection feature.

Sun Xtender Battery covers and containers are uniquely molded with high impact, reinforced copolymer polypropylene and are designed with thick end walls to prevent bulging. The copper alloy T Terminals are corrosion resistant and are supplied with silicon bronze bolts and washers.

All Sun Xtender Batteries ship Hazmat Exempt.

### PVX-3050T

Voltage	6v						
Industry Reference	GC2 Tall						
Battery Series	<a href="#">6 Volt Sun Xtender Series</a>						
Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 Volts per cell - 24 Hour Rate	305 Ah						
Weight	91 lb / 41.3 kg						
	Sun Xtender®	Length		Width		Height	
		in	mm	in	mm	in	mm

	Solar Battery							
	PVX-3050T	10.28	261	7.06	179	12.94	328.6	

Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell

1 Hr Rate	2 Hr Rate	4 Hr Rate	8 Hr Rate	24 Hr Rate	48 Hr Rate	72 Hr Rate	100 Hr Rate	120 Hr Rate	
190 Ah	245 Ah	270 Ah	280 Ah	305 Ah	335 Ah	348 Ah	354 Ah	358 Ah	

Specifications subject to change without notice.