



Request for Quote Form

Name: _____ Company: _____
Phone: _____ E-mail: _____

GENERAL

Capacity: _____ Manufacturer Preference: _____
Lift: _____

Suspension (Select One):

- Rigid Top hook Swivel Top Hook Lug mount
 Push trolley Hand-gearred trolley Motorized trolley

Voltage (Select One):

- 460-3-60Hz 230-3-60Hz 208-3-60Hz
 575-3-60Hz 115-1-60Hz 230-1-60Hz Other: _____

HOIST AND TROLLEY

Hoist speed: _____ Trolley speed (if Motorized): _____
Hoist control (Select One): Trolley speed control (If Motorized, Select One):
 Single Two-speed Variable Single Two-speed Variable

Beam flange width*: _____
Beam type: _____
Straight track / Curved track: _____ Minimum Radius (if curved): _____

Pendant required?
 No Yes – Length (Standard is 2-4 Feet less than lift): _____
Power cord required?
 No Yes - Length: _____

ENVIRONMENT AND DUTY CYCLE

Location of use: Indoor Outdoor Outdoor under roof
Hoist duty cycle (ASME): H3 H4
Special Application Requirements (i.e. food service, explosion proof, windmill):

Additional Details and Comments:

Project Urgency: Low Medium High QUOTE REQUIRED BY (Date): _____

*This field is required for all trolley suspensions

Please email to info@kistlerequipment.com
Or fax to 402-896-9474