



World Headquarters
601 Rayovac Drive
Madison, WI 53711
Telephone 1-800-331-4522
Internet www.rayovac.com

Marketing Data Sheet - Flashlights

S6600227
Issue B
Memo No: [MDSR0903](#)

Rayovac Stock Number: **ISL2D**

Name: **Industrial 2D Swivel Light**

Product Specifications

Power Source: Two D cells
Lamp: KPR102;
Rated at 2.40 volts, 0.70 amps
Lamp Life: Average of 15 hours
(at rated voltage) Minimum of 8 hours
Replacement Lamp: PR2, PR6, KPR102
Body Material: Polypropylene, TPE Cover
Lens Material: SAN
Lens Ring Material: Polypropylene, TPE Cover
Reflector Material: SAN
Switch Type: Slide
Length: 8.70 in; 221mm
Head Diameter: 2.62 in; 67mm
Body Diameter: 1.75 in; 44mm
Weight: 6.7 oz; 189 g (without batteries)



Performance Specifications

Run Time: 1.7 hours with Rayovac Heavy Duty D cells
11.5 hours with Rayovac alkaline D cells
Beam Brightness: 937 peak beam candlepower

Features

- Head swivels 90 degrees to aim beam where needed
- TPE (rubber) covers on body, end cap, and lens ring
- Hanging ring for convenient storage
- Faceted reflector provides bright, uniform spot
- Durable slide switch

Durability

- Withstands five foot drop tests
- Weatherproof construction

This data is subject to change. Performance information is typical. Contents herein do not constitute a warranty.