



## 05-09 MUSTANG REAR OVAL MEDALLION

### TOOLS NEEDED-

- Cotter Pin Puller
- Flat Blade Prying tool
- Philips head screwdriver
- Allen key (included)
- Fishing line

### REMOVAL

-Using a cotter pin puller, you want to get underneath the emblem through the keyhole and start to separate the medallion from the double sided tape. After it starts to pull away, use a prying tool to finish pulling it away from the car. You can use the key puller to assist in the removal.

-Remove the rest of the double sided tape, by using fishing line and use that to cut the adhesive from the vehicle.

-After the double sided tape is removed, clean the surface so that there is no sticky residue left over. You may use a rubbing alcohol or acetone to clean the surface.

### INSTALLATION

-Flip medallion base over install the three included rubber protectors to the backside of the medallion. Put one on the top of the medallion and the other two on each side of the medallion. This will allow the medallion not to scrape the paint on the back of the car.

- Place the two well nuts (flanged rubber with threaded inserts) in the two holes on the rear deck lid. Its going to be a tight fit, it may help to use a lubricated base liquid to help the rubber pieces fit in.

-Using the supplied M6x20 screws install medallion base onto the rear deck lid.

- Install medallion cover onto base with supplied 6/32x1/4 allen screws and allen key.

-Peel tape and install GT emblem onto medallion cover.