

Issue date March 1, 2015
Reviewed date October 1, 2020

Safety Data Sheet

SDS ID# 3040

Section 1. IDENTIFICATION

1.1. Product identifier

Product form : Pure
Product name : Methane, Compressed

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Calibration gas/Bumptest gas/Function test gas

1.3. Details of the supplier of the safety data sheet

Intermountain Specialty Gases
520 N. Kings Road
Nampa, ID 83687
Telephone 1-208-466-9425 or Toll free 1-800-552-5003
Fax 1-208-466-9144
www.isgases.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

Section 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification FLAMMABLE GASES - Category 1
: GASES UNDER PRESSURE - Compressed gas
SIMPLE ASPHYXIANTS - YES

2.2. Label elements

Hazard pictograms



Signal word : DANGER

Hazard statements : H220 - EXTREMELY FLAMMABLE GAS
: H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
: OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.
: CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR

: OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary statements

[General]	: Read and follow all Safety Data Sheets (SDS's) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have a product container or label at hand. Use equipment rated for cylinder pressure.
[Prevention]	: P202 - Do not handle until all safety precautions have been read and understood : P210 - Keep away from heat/sparks/open flames/hot surfaces - No smoking. : P271+P403- Use only outdoors or in a well-ventilated area : CGA-PG05 - Use a back flow preventive device in the piping. : CGA-PG10 - Use only with equipment rated for cylinder pressure. : CGA-PG12 - Do not open valve until connected to equipment prepared for use. : CGA-PG06 - Close valve after each use and when empty. : CGA-PG27 - Read and follow the Safety Data Sheet (SDS) before use.
[Response]	: P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. : P381 - Eliminate all ignition sources if safe to do so. : P304+P340+P313 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.
[Storage]	: CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)
[Disposal]	: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

No data available

Section 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%
Methane	(CAS No) 74-82-8	100

Section 4. FIRST AID MEASURES

4.1. Description of first aid measures

General	: IF exposed or concerned: Get medical advice/attention.
Inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. If

Skin contact	: Immediately flush with copious amount of water for at least 15 minutes.
Eye contact	: Immediately flush with copious amount of water for at least 15 minutes.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation section.

4.2. Most important symptoms/effects, acute and delayed

Acute

Inhalation	: May displace oxygen and cause rapid suffocation.
Skin contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Eye contact	: Contact with rapidly expanding gas may cause burns or frostbite.
Ingestion	: Ingestion is not considered a potential route of exposure, refer to the inhalation section.
Frostbite	: Thaw frosted parts with lukewarm water. Do not rub affected areas. Get immediate medical advice/attention.
Self-protection of the first aider	RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Remove all sources of ignition.
Symptoms	: Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere ($\leq 18\%$) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury
Chronic symptoms	: Adverse effects not expected from this product.
Delayed	: Adverse effects not expected from this product.

4.3. Indication of any immediate medical attention and special treatment needed

If victim feels unwell, seek medical advice. If breathing is difficult, give artificial respiration or oxygen by trained personnel.

Section 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical or CO ₂ . Water spray (fog). DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is flammable.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: None known.

5.3. Advice for fire-fighters

Firefighting instructions	: In case of fire: Evacuate all personnel from the danger area. Stop the leak and flow of gas before extinguishing fire, if safe to do so. If this is not possible, withdraw from
---------------------------	---

area and allow fire to burn. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Let the fire burn. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Exercise caution when fighting any chemical fire.

Protection during firefighting

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus, SCBA) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.

Section 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment

: Wear protective equipment consistent with the site emergency plan.

Emergency procedures

: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Escape the danger area by the closest safe route. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.12. For emergency responders

Protective equipment

: Standard protective clothing and equipment (e.g., Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.

Emergency procedures

: Evacuate and limit access. Ventilate area. See information above "For non-emergency personnel".

6.2. Methods and material for containment and cleaning up

For containment

: Immediately contact emergency personnel. Try to stop gas leak if safe to do so.

Methods for cleaning up

: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safety handling

: Pressurized container: Do not pierce or burn, even after use. Use equipment rated for cylinder pressure. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Protect cylinders from physical damage; do not drag, roll, slide, or drop.

Hygiene measures

: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: None known.

Storage conditions

: Do not expose to temperatures exceeding 52°C (125°F). Store locked up. Keep containers closed when not in use. Protect cylinder from physical damage. Store and use away from heat, sparks, open flame or any other ignition source. Store in well ventilated area.

Incompatible products

: None known.

Incompatible materials

: Oxidizing agents.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Methane (74-82-8)				
OSHA PEL		Cal/OSHA PEL	NIOSH REL	ACGIH 2015 TLV
ppm	mg/m ³	(as of 4/26/13)	(as of 4/26/13)	
		8-hour TWA	up to 10-hour TWA	8-hour TWA
		(ST) STEL	(ST) STEL	(ST) STEL
		(C) Ceiling	(C) Ceiling	(C) Ceiling
				1,000 ppm

8.2. Appropriate engineering controls

Engineering measures/controls : Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly check for leakages. Ensure exposure is below occupational exposure limits. Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures

Hand protection : Wear working gloves when handling gas containers. 29CFR 1910.138: Hand Protection.

Eye protection : Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing, e.g.-Lab coats, coveralls or flame resistant clothing.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Thermal hazard protection : None necessary during normal and routine operations.

Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Other information : Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Exposure controls

Appearance : Clear, colorless gas.

Physical state : Gas

Color : Colorless

Odor : No data available

Odor threshold : No data available

pH : No data available

Melting point : -182.5 °C / -296.5 °F

Freezing point : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable

Upper flammability : 15%

Lower flammability : 5%

Relative density : No data available

Solubility	: No data available
Partition coefficient	: No data available
Auto-ignition temperature	: 600 °C / 1112 °F
Decomposition temperature	: No data available
Viscosity	: Not applicable

	Methane			
Molecular weight (grams)	16.04			
Boiling point	-161.49 °C			
Vapor pressure	Above critical temperature			
Vapor density at 20°C	0.56			
Relative gas density	0.6784 kg/m ³ @ 20 °C			
Critical Temperature	-82.1 °C			

Section 10. STABILITY AND REACTIVITY

10.1. Reactivity

No reactivity hazard other than the effects described below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May form explosive mixtures with air. May react violently with oxidizers.

10.4. Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose container to heat or sources of ignition. Storage in poorly ventilated areas.

10.5. Incompatible materials

Extremely reactive or incompatible with the following: oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂)

Section 11. TOXICOLOGICAL INFORMATION

Acute toxicity

11.1. Information on routes of exposure

Inhalation	: This product is a simple asphyxiant.
Skin contact	: Adverse effects not expected from this product
Eye contact	: Adverse effects not expected from this product
Ingestion	: Ingestion is not considered a potential route of exposure

11.2. Symptoms related to physical, chemical and toxicological characteristics

Symptoms

Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere ($\leq 18\%$) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury

11.3. Delayed and immediate effects

Skin corrosion/irritation	: Contact with rapidly expanding gas may cause burns or frostbite.
Serious eye damage/irritation	: Contact with rapidly expanding gas may cause burns or frostbite.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: This product does not contain any carcinogens or potential carcinogens listed by OSHA, IARC or NTP
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
	Not applicable for gases and gas-mixtures

11.4. Carcinogenic effects

The components of this material are not found on the following lists: FEDERAL OSHA Z LIST, NTP AND IARC; therefore, they are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

Section 12. ECOLOGICAL INFORMATION

12.1. Aquatic Toxicity

Ecology - general : No ecological damage caused by this product

12.2. Persistence and degradability

No information available for the product

12.3. Bioaccumulative potential

No information available for the product

12.4. Mobility in soil

No information available for the product

12.5. Other





No information available for the product

Section 13. DISPOSAL CONSIDERATIONS

13.1. Disposal methods

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14. TRANSPORTATION INFORMATION

	US DOT	TDG	IMDG	IATA
UN #	UN 1971	UN 1971	UN 1971	UN 1971
Proper shipping name	Methane, compressed	Methane, compressed	Methane, compressed	Methane, compressed
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-
Environment	No.	No.	No.	No.

Section 15. REGULATORY INFORMATION

15.1. US Federal regulations

SARA 311/312 hazard categories

Acute Health : No
 Chronic Health : No
 Fire : Yes
 Pressure : Yes
 Reactive : No

SARA Title III Notifications and Information: Hydrogen is Listed under the accident prevention provisions of section 112[®] of the Clean Air Act (CAA) with a threshold quantity (TQ) of 10,000 pounds.

This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312	Sudden Release of Pressure Hazard
--------------	-----------------------------------

15.2. US State regulations

Methane (74-82-8)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right To Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right To Know) List

Section 16. OTHER INFORMATION

Date of issue/Date of revision 10/1/2020

Revision Note

Hazardous Material Information System (USA)

Hazard Scale : 0 = Minimal/ 1 = Slight/ 2 = Moderate/ 3 = Serious/ 4 = Severe

Health : 0

Fire	: 4
Physical hazards	: 3

Key/Legend

SARA	Superfund Amendments and Reauthorization Act
OSHA	Occupational Safety and Health Administration
DOT	Department of Transportation
TSCA	Toxic Substance Control Act
NTP	National Toxicology Program
ACGIH	American Conference of Governmental Industrial Hygienists
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TDG	Transportation of Dangerous Goods
CAS	Chemical Abstracts Service
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
TWA	Time Weighted Average
Prop	Proposition
ATE	Acute Toxicity Estimate

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose (s).