

## Clean Park® Limited Warranty

Auto Care Products, Inc. warrants your Clean Park® to be free from defects in material and workmanship for a period of three (3) years from the date of purchase for the 50 mil mat, and one (1) year for the 20 mil mat, subject to the following conditions and limitations:

### Conditions:

- This warranty only applies to the original purchaser of the Clean Park®.

### Limitations:

This warranty does not cover the following:

- Improper installation of the Clean Park®.
- Placement of the Clean Park® on any surface that is not smooth and flat.
- Improper use of the Clean Park®.
- Use with snow chains or studded snow tires.
- Punctures caused by rocks and other sharp objects.
- Use of Solvents, Chemicals and Detergents to clean the Clean Park®.
- Normal wear and tear.
- Discoloration of the vinyl sheeting that may occur over time.
- Tire impressions made on the vinyl sheeting, which is considered normal.

Should a defect occur, contact Auto Care Products, Inc. to request a Return Authorization Number. No returns will be accepted without a Return Authorization Number. It is the responsibility of the customer to pay for all shipping costs including insurance. Upon receipt of the returned part(s), Auto Care Products, Inc. will either repair or replace the defective part(s) as it deems necessary.

# Clean Park®



### Warning:

- The Clean Park® is Slippery When Wet.
- To use with Snow Chains or Studded Snow Tires, purchase Protector Strips from Auto Care Products, Inc.
- Do Not Turn Front Tires While Vehicle is Stationary on the Clean Park®.

For More Information Contact: **Auto Care Products, Inc.**  
 6345 Nancy Ridge Drive  
 San Diego, CA 92121  
 (800) 992-2018 or (858) 625-0005  
 Fax: (858) 625-0010  
 Email: [info@auto-care.com](mailto:info@auto-care.com)  
[www.autocareproducts.com](http://www.autocareproducts.com)



U.S. Patent #6,258,430

### Assembly Instructions

1. Sweep or vacuum garage floor. Repair or cover (with duct tape) any cracks in garage floor.
2. Lay out all of the edge pieces before beginning assembly.
3. See figure 1. Starting at the edge closest to the street, attach the long V-shaped pieces to the left and right sides.
4. See figure 2. On the end farthest away from the street, cut down vinyl sheet so it protrudes 1½" inches beyond the last long V-Shaped side piece.  
 NOTE: All Clean Parks® can be shortened by 2' increments just by omitting long V-Shaped side pieces and cutting the vinyl sheet, as described above.
5. See figure 3. On the side farthest away from the street, attach the short V-Shaped pieces.
6. See figure 4. Next, lay all of the flat parts, with the mushroom shaped profile, on the floor under the edge of the vinyl sheeting.
7. See figure 7. The ramp sections snap on top of the vinyl sheeting, onto the flat parts with the mushroom shaped profile. See figure 5 & 6. Each kit has two ramp sections with a rounded corner. Position the rounded corner next to the long V-shaped side pieces. Snap down the ramp sections with the rounded corners, on the left and right sides of the Garage Mat. Next, snap down the remaining top ramp sections.

### Warning:

**Rocks and other sharp objects may puncture the Clean Park®. To avoid punctures, regularly remove debris by sweeping with a soft bristle broom.**

### Cleaning Instructions:

Remove one or more of the end pieces closest to the garage door. Be careful not to puncture or cut the vinyl sheeting with the edge of the top piece as you pull it off. Sweep the Clean Park® with a soft bristle broom. Hose off the Clean Park®. Use a soft bristle broom to push water towards the open area, off of the Clean Park®. Only a mild dish soap may be used on the Clean Park®. Do Not Use Solvents, Harsh Chemicals, Abrasive Cleaners or Bleach. Discoloration of the vinyl sheeting may occur over time and does not affect the integrity of the material.

### Cold Weather Assembly Tip

In extremely cold weather, the vinyl sheet may become stiff, making it difficult to attach the edge pieces. To soften up the vinyl sheet, bring the vinyl sheet inside the house and allow it to warm up to room temperature.

Or

Use a hair dryer and blow warm air along the vinyl sheet, as you attach each edge piece.  
**DO NOT USE A HEAT GUN**

