



Garner HD-2

HD-2 Features:

- *Easy to Use Drawer*
- *Continuous duty*
- *50 second cycle time*
- *Light weight (42 lbs.)*
- *One button Operation*
- *Complete erasure of high coercivity hard drives & tapes*
- *Audio Verification*
- *Solid State Design*
- *Micro-processor controlled*



Optional shipping/transportation case: Eliminate the risk of information loss during media transportation. Transport the HD-2 degausser directly to the location of your media.

The HD-2 is the newest and most innovative product in the Garner line of degaussers. The HD-2 erases hard drives (laptop, desktop and network up to 1" high) and high coercivity tape media, including all formats of LTO (1,2,3,4), SuperDLT I & II, DLT, 9940, 3590, AIT, 8mm and more, all without any adapters. With a continuous duty rating (no cooling necessary) quiet operation and a 50 second cycle time, the HD-2 can be used right on a desktop.

HD-2 Operations:

The HD-2 is exceptionally user-friendly. Simply place your media into the drawer on the right side of the HD-2 and push the "Erase" button. Within 50 seconds your media is completely erased. Open the drawer and remove your erased media. It just doesn't get any easier than that!

Safeguards:

The HD-2 has been independently tested and certified to meet both ANSI and CE standards. Built-in safeguards check the stored power before each erase cycle ensuring complete erasure every time. Audible tones and lighted push buttons report the status of the HD-2 to the operator.

Degauss vs. Overwrite:

The HD-2 produces an erasing field many times stronger than the erasing fields produced by the read/write heads in hard drives and tape drives. The field strength along with the encompassing magnetic field ensure the data is no longer recoverable by computer or laboratory attacks. Since the HD-2 does not rely on software, the HD-2 will also completely and permanently erase failed and damaged hard drives regardless of the operating system or interface.

Government Mandates:

The HD-2 will assist you in meeting compliance standards for government mandates requiring complete elimination of sensitive information stored on magnetic media prior to re-use or disposal including:

- **PCI DSS** (Payment Card Industry) Data Security Standard
- **NIST** (National Institute of Standards and Technology) Guidelines for Media Sanitization
- **NIST SP 800-36**
- **NIST SP 800-88**
- **HIPAA** (Health Information Portability and Accountability Act)
- **PIPEDA** (Personal Information Protection and Electronic Documents Act)
- **GLBA** (Gramm-Leach-Bliley Act)
- **California Senate Bill 1386**



| SPECIFICATIONS | |
|-------------------|--|
| Power Supply | 120V ±5%, 50/60 Hz - Standard |
| Power Consumption | Under standby 0.2A While charging 15.0A < 1 second At the time of ERASE 0.5A |
| Degausser System | Capacitive Discharge |
| Duty Cycle | Continuous |
| Erasure Time | 50 second repetitive cycle |
| Magnetic Field | 7,300 Oe, .73 Tesla |
| Erasing Area Size | 1.0 in. (H) x 4.5 in. (W) x 6.75 in. (D) |

| SPECIFICATIONS | |
|----------------|--|
| Media | Hard drives up to 1.0" high including full height, standard and laptop drives, tape cartridges including DLT, LTO, 3590, 8mm and more. |
| Temperature | 41°F - 104°F (5°C - 40°C) |
| Humidity | 10%H - 40%H (without condensation) |
| Weight | HD-2: 42 lbs. (19 Kg) Shipping: 49 lbs. (22.25 Kg) |
| Size | L x W x H inches. 12.25 x 17.50 x 7.25 in. |
| Warranty | 1 Year Factory Warranty Standard, Optional 3 Year Factory Warranty available. |

Note: Hard Drives and some tapes are not reusable after having been erased with the HD-2.