





High Efficiency Toilets operate in the range of 1.1gpf to 1.6gpf (4.2Lpf to 6.0Lpf)

Flush Valve Toilets Vitreous China	FIXTURE NO.	DESCRIPTION	WEIGHT	PTS.	CU. FT/CTN. PLT. QTY.	LIST PRICE	AVAILABLE COLORS
	MADERA YOUTH™ FloWise® 14" HEIGHT ELONGATED FLUSHOMETER TOILET						020 White
	<ul style="list-style-type: none"> • Elongated floor mount flushometer valve toilet, top spud, less seat • High Efficiency, Low Consumption operates in the range of 1.28gpf to 1.6gpf (4.8 Lpf to 6.0 Lpf) • Meets definition of HET (High Efficiency Toilet) when used with a high efficiency flush valve (1.28 gpf) • Fully glazed 2-1/8" trapway • Elongated bowl • 10" or 12" roughing-in • 14" rim height • Condensation channel • Powerful direct-fed siphon jet action • 10" x 12" water surface area • 1-1/2" inlet spud • 2 bolt caps • 100% factory flush tested • TAS Compliant <p>Nominal Dimensions: 28-1/4" x 14" x 14" (718 x 356 x 356mm)</p> <p>Recommended working pressure-- between 25 psi at valve when flushing and 80 psi static</p>						
 <p>When used with 1.28 gpf flush valves</p>	2599.001	<ul style="list-style-type: none"> • Elongated bowl only, top spud 	56.4 lbs (25.5 kg)	1.7	3.74 18	208.00	
	<ul style="list-style-type: none"> ▷ 047007-0070A ▷ 481310-0200A 	<p>Available Component Parts:</p> <ul style="list-style-type: none"> • Inlet spud (furnished with bowl) • Bolt caps with retainers (furnished with bowl) <p>TAS Compliant Recommended Seats (sold separately):</p>				26.00 5.00	
	5901.100	<ul style="list-style-type: none"> • For ages 5 through 8: Elongated, heavy-duty, open front toilet seat, less cover, with stainless steel check hinge 	3 lbs (1.5 kg)			45.00	
	5905.100	<ul style="list-style-type: none"> • For ages 9 through 12: Elongated, extra heavy-duty, open front toilet seat, less cover, with stainless steel check hinge 	3 lbs (1.5 kg)			56.00	
	5910.100	<ul style="list-style-type: none"> • For ages 9 through 12: Elongated, extra heavy-duty plus, open front toilet seat, less cover, with stainless steel check hinge 				56.00	
		<p>See 2012 American Standard Pricing Guide pages C41-C49, C57-C58 for Flush Valves.</p>					
		<p>MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES</p>					

▷ Repair Part
Meets all ANSI / ASME Low-Consumption, Water Conservation Requirements