

CSM-1

Wireless presentation and collaboration system



ClickShare makes connecting to the meeting room's video system a matter of clicking a button. This one click wonder not only helps the presenter get the presentation on-screen in a second, but it also allows the other people in the meeting to participate more actively. The result is enhanced meeting efficiency and better decision-making.

How it works

A ClickShare CSM-1 set consists of two USB-powered devices (the 'ClickShare Buttons') and a Base Unit. The Base Unit has a fixed connection to the meeting room's visualization system, and takes care of all the needed processing. Users who want to get their presentation on the large meeting room screen, simply connect a Button to their PC or MAC. They start the application, click the ClickShare Button and immediately their desktop is wirelessly transferred to the large visualization system. What's more, CSM-1 does not interfere with your laptop's resolution, and automatically displays the screen content in the most optimal way.

Confidence and collaboration

ClickShare simply works. This sounds obvious, but considering all the time lost today trying to connect the laptop to the meeting room display, it means a big relief for presenters. The result is enhanced confidence, leading to better presentations. Using the ClickShare app for Android or iOS, users can also get the content from their tablet or smartphone on the meeting room screen using ClickShare.

BARCO

Visibly yours

Technical specifications

CSM-1

General specifications	
Operating system	Windows XP/Vista/7/8 32 & 64 bit Mac OSX 10.6/10.7/10.8 Android 2.2 and later (ClickShare mobile app) iOS 5.0 and later (ClickShare mobile app)
Video outputs	HDMI (video and audio)15-pin VGA
Frame rate	Up to 30 fps depending on environment
Output resolution	HDMI: 1280x720 (720P), 1920x1080 (1080i/1080p) VGA: (SVGA (800x600) / XGA (1024x768) / WXGA(1280x768) / WXGA+(1280x800) / 1360 * 768 / 1440 * 900 / 1600 * 1200
Input Resolutions	Up to 2048x1536 (QXGA)
Number of sources simultaneous on screen	1
Number of simultaneous connections	8
Audio	Radio quality 16bits 22KHz (no synchronization) via audio jack or HDMI
iPad, iPhone and Android compatibility	Available via ClickShare app for static content.
Authentication protocol	WPA2-PSK
Wireless transmission protocol	IEEE 802.11 a/b/g/n
Data rate wireless	Up to 300Mbps
Reach	Max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit, depending on environment
Band	2.4 GHZ and 5 GHz
Power	External Power adaptor 5V DC input 2.6A (included in set)
Connections	USB Host x 2 RJ-45 LAN Port Audio analog line out on mini jack socket (3.5mm)
Temperature range	Operating: 0°C to +40°C (+32°F to +104°F) Storage: -10°C to +60°C (+14°F to +140°F)
Humidity	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 80% relative humidity, non-condensing
Wall mounts	Included in set
Certifications	FCC/CE
Warranty	3 years standard
ClickShare Base Unit dimensions	
Dimensions (HxWxD)	Excl. antennas: 37mm x 186mm x 85mm / 1.457" x 7.323" x 3.346" Incl. antennas: 125mm x 186mm x 121mm x / 4.921" x 7.323" x 4.763"
Weight	530g / 1.17lbs (incl. antennas)