

Pro L20000UNL WUXGA 3LCD Laser Projector Without Lens

Projectors

Large Venue



Product shown with lens.
Lens sold separately.

Premium large-venue WUXGA laser projector with 20,000 lumens¹.

Ultra bright, vivid color — 20,000 lumens color/white brightness¹; advanced 3-chip, 3LCD technology

Exceptional widescreen display — Full HD WUXGA (1920 x 1200) resolution; accepts 4K content and provides 2.3 million pixels on screen

Solid-state laser light source — with electrostatic air filter for up to 20,000 hours of virtually maintenance-free operation²

Wide range of optional lenses (sold separately) — including a zero-offset ultra short-throw lens

Powerful — outstanding brightness from a remarkably compact large-venue projector

Advanced connectivity — two interface slots accommodate a wide range of inputs

Designed for demanding environments — features a sealed light source and optical engine for outstanding durability for live events and fixed installations

Dynamic projection capabilities — with advanced tools like tiling assist, Edge Blending and auto-color adjustment for fast installation; free software for multi-projector setup

Bold, vibrant images — supports High Dynamic Range (HDR) via HDR10³ (PQ) and Hybrid Log Gamma (HLG); BT.709 color space

Mechanical shutter — protects against damage from external laser lights

Frame interpolation — ideal for fast-moving images

Wide lens shift — optimized lens and optical engine design



Specifications

Projection System High-aperture Epson® 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Native Resolution WUXGA (1920 x 1200)
Resolution on Screen WUXGA / 2.3 million pixels
Pixel Number in Device 2,304,000 pixels (1920 x 1200) x 3 chips
Signal Input
 Maximum display resolution 1920 x 1200.
 Display resolution 1920 x 1200 pixels
Aspect Ratio 16:10, 16:9, 4:3
Pixel Arrangement Cross stripe
Color Brightness¹ Color Light Output: 20,000 lumens
White Brightness¹ White Light Output: 20,000 lumens
Contrast Ratio 2,500,000:1
Brightness Uniformity (Typical) 90%
Color Reproduction Up to 1.07 billion colors
Keystone Correction Vertical: ±44 degrees; Horizontal: ±30 degrees
Illumination Technology Laser Diode
Light Source Life²
 20,000 hours (Normal); 30,000 hours (Extended)
Projection Lens (Standard, Not Included)
 See website for information on optional lenses.
ELPLM15 Lens
Type Powered shift/focus/zoom
F-number 1.8 – 2.35
Focal Length 36.0 – 57.4 mm
Zoom Ratio Optical zoom 1 – 1.6x
Throw Ratio Range 1.57 – 2.56
Lens Shift Vertical: ±60 percent; Horizontal: ±18 percent

Other Features


Operating Temperature 32° to 113° F (0° to 45° C)
Power Supply Voltage 100 – 120 V AC, 200 – 240 V AC
 +/-10%, 50/60 Hz; Requires 200-240 V for full spec. operation
Power Consumption
 1860 W (Normal/Custom Mode)
 1123 W (Extended/Eco Mode)
 2.0 W Standby (Communication on)
 0.5 W Standby (Communication off)
Fan Noise 45 dB (Normal Mode); max. 38 dB (Quiet Mode)
Security Security cable hole, Kensington lock provision

Video I/O

Input Signal Input Video Signal (HDMI, DVI-D and HDBaseT ports)
 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/4096 x 2160

Interfaces

3G-SDI x 1 (SDI out x 1 - Active through)
 HDBaseT x 1
 5-BNC
 VGA x 1
Interface (Slot 1)
 ELPIF01 (included from factory)
 DVI-D x 1
 HDMI® x 1 (HDCP2.2)
 DC Out (500 mA)
Interface (Slot 2)
 Blank from factory
Interface Card (optional)
 ELPIF03
 Display Port x 2 (DP 20p)
Other
 USB connector Type B x 1: for Firmware update, Copy OSD Settings
 USB connector Type A x 1: for Firmware update, Copy OSD Settings, DC Out 900 mA
 Monitor out: Mini D-sub 15-pin x 1
 Serial: RS-232c x 1
 Remote: Stereo mini
 Wire LAN x 1 etherCON



Dimensions (W x D x H)

Dimensions (Including feet, lens) 24.4" x 14.1" x 31.1"
 (620 x 358.5 x 790 mm)
Weight 109.3 lb (without standard lens, not included)

Remote Control

Features Power, Search Selection, Lens Shift, Zoom, Focus, Test Pattern Selection, Shutter, Freeze, User ID, Auto, Aspect, Color Mode, Menu, Slot 1, Slot 2 and more
 Right/Left: Front: ± 50 degrees; Rear: ± 40 degrees
 Upper/Lower: Front: ± 50 degrees; Rear: +30 degrees
Operating Distance 49 ft

Eco Features

RoHS compliant
 Recyclable product⁴
 Epson America, Inc. is a SmartWay® Transport Partner⁵

Support

Epson ConnectionSM
 Pre-sales support: U.S. and Canada 800-442-1977
 Internet website: www.epson.com

Service Programs

The projector has a limited warranty of 3 years or 20,000 hours, whichever comes first.

What's in the Box

Pro L20000UNL projector, power cables (3m 100v and 3m 200v), projector remote control with batteries, quick reference sheet

Ordering Information

Pro L20000UNL	V11H833820
Replacement Air Filter (ELPAF58)	V13H134A58
HDMI/DVI-D Interface Board (ELPIF01)	V12H917F01
Display Port Interface Board (ELPIF03)	V12H916F01
Ultra Short-throw Lens (ELPLX02)	V12H004X02
Ultra Short-throw Lens – White (ELPLX02W)	V12H004Y02
Short-throw #1 Zoom Lens (ELPLU03S)	V12H004UA3
Short-throw #2 Zoom Lens (ELPLU04)	V12H004U04
Wide-throw #3 Zoom Lens (ELPLW08)	V12H004W08
Wide-throw #2 Zoom Lens (ELPLW06)	V12H004W06
Middle-throw #2 Zoom Lens (ELPLM15)	V12H004M0F
Middle-throw #3 Zoom Lens (ELPLM10)	V12H004M0A
Middle-throw #4 Zoom Lens (ELPLM11)	V12H004M0B
Long-throw Zoom Lens (ELPLL08)	V12H004L08
Epson Ceiling Mount – Low Ceilings (ELPMB47)	V12H802010
Epson Ceiling Mount – High Ceilings (ELPMB48)	V12H803010

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. Some lenses will not support the maximum brightness level of this projector. | 2 No required maintenance for the light source and filter up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 3 HDR performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 4 For convenient and reasonable recycling options, visit www.epson.com/recycle | 5 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future™
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. Epson Connection is a service mark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2019 Epson America, Inc. Com-SS-Oct-13 CPD-56519R1 11/19

