

TM03 5535 0907

Flow range: 0-17 gpm  
 Head range: 0-19.5 feet  
 Motors: 2-pole, single-phase  
 Max. liquid temperature: 230 °F (110 °C)  
 Min. liquid temperature: 36 °F (2 °C)  
 Max. system pressure: 145 psi (10 bar)




Model	Spd	Volts	Amps	Watts	Hp	Capacitor
UPS 15-58 FC/FRC	3		0.75	87	1/25	
	2	115	0.66	80	1/25	10µF/180 V
	1		0.55	60	1/25	


—	Without check valve
- - -	With check valve

UPS 15-58 FC

UPS 15-58 FRC



TM03 8757 2407



TM03 8531 1907

### Approvals



Model type	Product number	Dimensions [inches]						Connection type and size	Shipping weight [lbs]
		A	B	C	D	E	F		
UPS 15-58 FC	59896341	6 1/2	5 1/4	4	4 3/16	3	3 5/32	GF 15/26 flange (2) 1/2" dia. bolt holes	7 1/4
UPS 15-58 FRC	59896343	6 1/2	5 1/4	4	4 3/16	3	3 5/32	GF 15/26 flange (2) 1/2" dia. bolt holes	7 1/4

**Note:** The check valve can be removed.  
 Dimensions in inches unless otherwise noted.