


Ceramic Filters Company, Inc.

A-2 Fluoride Reduction Element

These filter elements are designed to reduce fluorides in drinking water to below 0.5 ppm. They are constructed with materials which are FDA approved.

The A-2 filter element uses activated alumina that has been especially prepared for the reduction of fluorides in drinking water. Laboratory tests show that this preparation will improve the capability of the filter to reduce the fluoride levels from 10 ppm F+ to below 0.2 ppm F+. Normal total capacity of the A-2 is over 8,000 ppm F+.

Performance of the A-2 will be degraded by flow rates in excess of 0.25 gpm, high pH or high bicarbonate supply water. If the supply water tests above 100 ppm of bicarbonate, the fluoride reduction will be degraded to less than 50%; if the supply is over 200 ppm, the reduction efficiency is less than 75% of normal.



- Available in 2" diameter with Doulton threaded end or 9³/₄" cartridge for standard 10" housings & 20" housings.
- 10" element should be changed every 400 gallons or approx. every 6 months
- 9³/₄" cartridge element should be changed every 600 gallons or approx. 9 months.
- Big Blue 10" and 20" cartridges available

- The A-2 element has also been shown to reduce arsenic to less than 0.02 ppm from 0.12 ppm in the supply water. Total capacity for arsenic has not been determined.