Millennium-Filters.com
QUALITY OEM REPLACEMENT FILTERS

# HYDAC/HYCON 0110D010BN3HC 10µm, Pleated Microglass Media

| Product Attribute | Specifications |
|---|---|
| Filter Type: | Hydraulic Filter Cartridge |
| Media Type: | Pleated Microglass Media |
| Overall Height: | 6.02” |
| Outer Diameter: | 1.85” |
| Inside Diameter - Bottom: | 0.87” |
| Collapse Pressure: | 435 PSI [Available in High Collapse Version 3045 psi] |
| Operating Temperature: | -13° to 250°F |
| Filter Area: | .95 Square Feet |
| Direction of Flow: | OUTSIDE – IN |
| Seal Material: | VITON |
| Micron Rating: | 10 |
| Beta Ratio: | 200/13 |

| MEDIA Available | Micron Ratings available |
|---|---|
| Pleated Microglass Media | 3-micron, 5µm, 10µm, 20µm<br>Water Removal Media Available |
| Pleated Paper Media | 3-micron, 5µm, 10µm, 20µm |
| Stainless Steel Wire Mesh Media<br>(304 SS) | 10-micron, 25µm, 50µm, 80µm<br>100µm, 125µm, 149µm, 200µm, 250µm |
| Sintered Fiber Media | 3-micron Sintered-Fiber, 10-micron SF,20-micron SF |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.

www.Millennium-Filters.com 24855 NOVI ROAD Suite 105 NOVI, MICHIGAN 48375 Phone: 248-719-7441 Fax: 248-869-6090