



QuickSet-SP Semi-Permanent Recreational Volleyball System

Uprights shall be constructed of 2"x2"x 11 ga. steel tubing. Upper height adjustable post section on each upright shall slide up and down inside lower upright section allowing net height adjustments anywhere from 7' 11 5/8" (men's volleyball) down to 72" for juniors. Lower upright section shall be powdercoated black to protect against the elements. Upper telescoping section shall be galvanized silver.

The net shall be one meter high, be constructed of black polypropylene 3.5mm knotless woven webbing, have a Kevlar top rope and polypropylene bottom rope. The top rope shall rest in a groove of a 4" diameter steel pulley at the top of the winch standard for ease of net tensioning. The top, bottom and sides of the net shall be finished with white tarpaulin fabric with double stitched hemmed edges. The top of the net shall be tensioned by means of a high tension rope ratchet. Net bottom rope shall be tensioned by means of a ratcheting style tensioner.

Net height shall be adjustable from 7' 11 5/8" (men's volleyball) down to 72" for junior heights.

Each standard shall be padded to a minimum height of 72" with 1 1/2" thick high density foam covered with vinyl in customer's choice of 12 school colors.

Floor/Ground plates shall be constructed of chrome plated steel with hinged lid. Floor/Ground sockets shall be welded steel powder coated black. Floor/Ground sockets and lids shall be designed to be used either indoor gymnasium or outdoor grass/concrete courts.

Upright standards shall carry no less than a Lifetime Limited Warranty. All other components shall carry a 2-Year Limited Warranty.

Entire QuickSet-SP system shall weigh 130 lbs.