

Threshold with Flexible Joint

Threshold Flexes or Expands for a Variety of Uses

The Pemko 573x5_FG threshold is a commercial threshold with a flexible joint. The flexible joint allows the threshold to flex as much as 20 degrees up or down, or to expand up to an additional 1/4". Ideal applications include uneven floor surfaces or building components that expand and contract, or move slightly, such as a floating ramp or an expansion joint.


The flexible joint is made from a thermoplastic elastomer that adds an additional benefit as a thermal barrier. A thermal barrier threshold doesn't allow heat to be transferred from one side of the threshold to the other, which would normally cause condensation.

Applications:

- Office Buildings
- Healthcare Facilities
- Public Buildings
- Retail
- Special Applications

Features	Benefits
Flexible joint flexes the threshold 20° up or down	Suitable for uneven or floors that expand and contract slightly
Thermally broken threshold	Prevents temperature transfer and condensation
Low profile for ADA compliance	Enables easy access to facility
6063-T6 aircraft aluminum	Durable & long lasting


© 2015 Pemko Manufacturing Company



ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience

Available Products

Part Number	Length	Finishes
573x5AFG	10" to 10 1/4"	Mill Finish Aluminum
573x5DFG	10" to 10 1/4"	Dark Bronze Anodized Aluminum



The 573x5 threshold flexes +/- 20° to allow for expansion or contraction of building materials

Technical Specifications:

Material:
6063-T6 Aircraft Aluminum

Insert Material:
Black PemkoPrene®

Finishes:
Mill Finish, Dark Bronze Anodized

Fasteners:
#10 x 1" Sheet metal screws

ADA Compliance: Meets the barrier free requirements of ICC/ANSI A117.1-2009 and ADAAG-2010 (amended), when used the slope is not steeper than 1:2, and the overall height is 1/2" or less, and all other applicable criteria are met.

GreenGuard Gold Certification: Meets the product certification requirements for low chemical emissions of UL 2818 to Gold status.



For more information about GREENGUARD and GREENGUARD Gold certification, visit www.ul.com/gg.



ASSA ABLOY is a member of the USGBC and CaGBC. U.S. Green Building Council logo is a trademark owned by the U.S. Green Building Council and is used with permission.



MEMPHIS, TN USA
P: 800 824-3018
F: 800 243-3656

VENTURA, CA USA
P: 800 283-9988
F: 800 283-4050

VANCOUVER, BC CA
P: 877 535-7888
F: 877 535-7444

TORONTO, ON CA
P: 877 535-7888
F: 877 535-7444

Pemko Manufacturing Company
websales@pemko.com
www.pemko.com